



Enclosure 300H x 300W x 150D Steel, RAL 7035 (GREY)

Features:

- 1.5mm Galvanised Steel
- RAL 7035 (Grey)
- IP66 rated
- Includes Back Mounting Plate & Mounting Clips, Glands

Specifications

| | |
|-----------------------------|---|
| Ordering Code | RODN303015 |
| Custom Tariff number | 85.38.10.00 |
| Construction Material | Galvanised Steel 1.5mm Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts |
| Application | |
| Mounting | Wall Mounted Cabinet |
| Cable Entry | 3 x M20 cable glands |
| Colour | RAL 7035 (Grey) |
| Finish | Hardened Polyester Paint, Textured, UV protection |
| Door Type | Single, Hinged |
| Lock Type | 1 x Twist Lock |
| Sealing Gasket | Injected Polyurethane Sealing gasket |
| Mounting Plate | With flat mounting plate. 1.5mm galvanised sheet steel |
| Maximum Operational Voltage | 1000VAC/1500VDC |

Cabinet External & Installation Dimensions

| | |
|----------------------------|---|
| External Dimensions (mm) | 300H x 300W x 150D |
| Usable Internal Space (mm) | 250H x 250W x 110D |
| Panel Thickness | 1.5mm Galvanised Steel |
| Back Mounting Plate Size | 246W x 280H |
| Wall fixing (mm) | 240H x 330W |
| Cabinet Net Weight(kgs): | 6.45 kgs |
| Cabinet Gross Weight(kgs): | 6.86 kgs |
| Package Dimension(mm) | 345W x 210D x 350H |
| Hardware | Supplied Fully assembled- 4pcs wall mount bracket , 4pcs Dynabolts, 1pcs key |

Protection & Standards

| | |
|----------------------|------------------------|
| Standards | IEC 62208, IEC 61439-1 |
| Degree of Protection | IP66 |
| Sustainability | ROHS – REACH |