

Test Report

Report Number:
250251-34-NDS



**DANISH
TECHNOLOGICAL
INSTITUTE**

Gregersensvej 1
DK-2630 Taastrup
+45 72 20 20 00
info@teknologisk.dk
www.teknologisk.dk

Page 1 of 6
Init.: JNAS/OJGC
Order no.: 250251
Encl.: 2

Assignor:	FREDERICIA FURNITURE A/S, Treldevej 183, DK-7000 Fredericia
Item:	6073 MK73 Cabinet - the test also covers the following model nos.: 6054, 6055, 6056, 6066, 6067 and 6068.. See enclosure B for detailed sample description.
Sampling:	The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 20 October 2025.
Period:	The test took place from 22 October 2025 to 12 November 2025.
Method:	EN 16121:2023/AC:2025 - Non-domestic storage furniture - Requirements for safety, strength, durability and stability Test severity 1: General: hotels, homes for the elderly, kindergarten, reception areas, meeting rooms, lounge areas, restaurants, laboratory furniture. Additional test methods that are referred to are listed in enclosure B.
Test results:	Passed. The detailed results are shown in enclosure A.
Terms:	This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2017) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent. Storage: The test material will be destroyed after 1 month, unless otherwise agreed.
Place:	Danish Technological Institute, Taastrup, Building and Construction
Signature:	This document is only valid with a digital signature from Danish Technological Institute. The date of issue appears from the digital signature. Jacob Næsby Consultant



DANAK
TEST Reg.no. 2



Results

Safety requirements

Test No.	Test	Result
5.2	General requirements	Passed
5.3	Holes in tubular/rigid components	Passed
5.4.1	Shear and compression points when setting up and folding	N/A
5.4.2	Shear and compression points under influence of powered mechanisms	N/A
5.4.3	Shear and compression points during use	Passed
5.5	Hinged horizontal lids	N/A
5.6	Vertical glass components	N/A

Stability

Test No.	Test	Test Method	Loading		Result
5.7.1	Doors, extension elements and flaps closed, all storage units unloaded - Units that are, or can be, adjusted to a height of 1000 mm or less	EN 16122, 11.2.1	Vertical force, N	750	N/A
5.7.2	Doors, extension elements and flaps closed, all storage units unloaded - Units that are, or can be, adjusted to a height of more than 1000 mm	EN 16122, 11.2.2	Vertical force, N Outward force, N	350 50	N/A
5.7.3	All storage areas unloaded and all doors, extension elements and flaps open	EN 16122, 11.4.1	-	-	N/A
5.7.4	All storage areas unloaded with overturning load	EN 16122, 11.4.2	Vertical force, N	75	N/A
5.7.5	All storage areas loaded with overturning load	EN 16122, 11.4.3	Vertical force, N		N/A
5.7.6	Doors, extension elements and flaps closed and locked	EN 16122, 11.5	Outward force, N	100	N/A
5.7.7	Dynamic stability test for units with castors	EN 16122, 11.6	-	-	N/A



Structural safety

Test No.	Test	Test Method	Loading	Result
5.8.1.1	Static load test for tops and bottoms	EN 16122, 6.2.2	Force, N Cycles 1000 10	Passed
5.8.1.2	Shelf retention test - horizontal outward	EN 16122, 6.1.2	Force, N	N/A
5.8.1.3	Shelf retention test - vertical downward	EN 16122, 6.1.3	Force, N 100	Passed
5.8.1.4	Strength of shelf supports	EN 16122, 6.1.5	Cycles Mass per unit area, kg/dm ² Total mass used, kg 10 0.65 10.3	Passed
5.8.1.5	Vertical load on pivoted doors	EN 16122, 7.1.2	Mass, kg Cycles 30 10	Passed
5.8.1.6	Horizontal load on pivoted doors	EN 16122, 7.1.3	Force, N Cycles 60 10	N/A
5.8.1.7	Strength of bottom-hinged flaps	EN 16122, 7.3.1	Force, N Cycles 200 10	N/A
5.8.1.8	Strength of extension elements	EN 16122, 7.5.2	Force, N Cycles 200 10	N/A
5.8.1.9	Slam open of extension elements	EN 16122, 7.5.4	Velocity, m/s 1.3	N/A
5.8.1.10	Interlock test	EN 16122, 7.5.6	Force, N Cycles 200 10	N/A
5.8.1.11	Test for structure and underframes	EN 16122, 6.4.1	Force, N Cycles 350 10	N/A
5.8.1.12	Test for unit with castors or wheels	EN 16122, 6.4.3	Cycles 2000	N/A
5.8.1.13	Overload test	EN 16122, 10.1.3	Mass per unit area, kg/dm ² Total mass used, kg 2.5 112	Passed
5.8.1.14	Dislodgement test	EN 16122, 10.1.4	Force, N 100	Passed
5.8.1.15	Units supported by the floor	EN 16122, 10.2	Force, N 200	N/A



Strength and durability

Requirements in accordance with EN 16121 Severity 1

Test No.	Test	Test Method	Loading	Result
6.1.1	Strength of cloth rail supports	EN 16122, 6.3.1	Mass per unit length, kg/dm Time, h	4 1 N/A
6.1.2	Strength of coat hooks	EN 16122, 9.1	Force per hook, N Cycles	40 10 N/A
6.1.3	Durability of pivoted doors	EN 16122, 7.1.5	Cycles	40000 Passed
6.1.4	Slam shut test of pivoted doors	EN 16122, 7.1.4	Mass, kg Cycles	3 10 Passed
6.1.5	Slam shut/open of sliding doors and horizontal roll fronts	EN 16122, 7.2.2	Mass, kg Cycles	3 10 N/A
6.1.6	Durability of sliding doors and horizontal roll fronts	EN 16122, 7.2.3	Cycles - sliding doors Cycles - roll fronts	20000 10000 N/A
6.1.7	Durability of flaps	EN 16122, 7.3.2	Cycles	10000 N/A
6.1.8	Durability of vertical roll fronts	EN 16122, 7.4.2	Cycles	10000 N/A
6.1.9	Durability of extension elements	EN 16122, 7.5.3	Cycles - extension elements Cycles - trays	40000 20000 N/A
6.1.10	Slam shut of extension elements	EN 16122, 7.5.4	Velocity, m/s	1 N/A
6.1.11	Displacement of extension element bottoms	EN 16122, 7.5.5	Force, N Cycles	60 10 N/A
6.1.12	Strength test for locking and latching mechanisms for extension elements	EN 16122, 7.6.2	Force, N Cycles	200 10 N/A
6.1.13	Strength test for locking and latching mechanisms for doors, flaps and roll fronts	EN 16122, 7.6.3	Force, N Cycles	200 10 N/A
6.1.14	Drop test	EN 16122, 6.4.2	Drop height, mm	 N/A
6.1.15	Deflection of shelves	EN 16122, 6.1.4	Mass per unit area, kg/dm ² Total mass used, kg	1 25.2 Passed
6.1.16	Dislodgement of clothes rails	EN 16122, 6.3.2	Mass per unit length, kg/dm Total mass used, kg	5 N/A
6.1.17	Drop test for trays	EN 16122, 8.3	Drop height, mm Cycles	350 10 N/A
6.1.18	Sustained load test for trays	EN 16122, 8.2	Kg/dm ² Total mass used, kg	0.65 N/A

Documentation

Test No.	Test	Result
7	Information for use	Passed



Methods

The following standard methods are used in this test report:

EN 16121:2023/AC:2025 - Non-domestic storage furniture - Requirments for saftey, strength, durability and stability

EN 16122:2012 - Domestic and non-domestic storage furniture - Test methods for determination of strenght, durability and stability

Measurement uncertainty: Decision rule according to EN ISO IEC 17025:2018 clause 3.7: No account is taken of measurement uncertainty when reporting numerical results.

Sample

Description of the item tested:

Model:	6073 MK73 Cabinet
Type:	Cabinet
Width:	760 mm
Height:	761 mm
Depth:	361 mm
Weight:	19.24 kg
Materials:	Oak
Mounting:	Wall mounted



Photo of the sample as received:

