

DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK EXPERT

Betek Expert is a vinyl-acrylic, water-based, VOC compliant, decorative final coat interior paint which offers perfect color tones on applied surfaces with maximum coverage, whiteness, water carrying structure and unique smooth functional matt texture.

SPECIFICATIONS

Betek Expert differentiates in ceiling and Wall applications with its unique functional matte texture. It has a unique smooth texture thanks to the special fillings in its formula. Thanks to its superior whiteness and hiding power, it is also suitable for painting the ceilings. Has high water holding ability. Integrates with the application surface. No blistering and flaking. Provides saving from labor thanks to its easy-to-spread texture. No disturbing odor due its water-based formula and environment-friendly.

APPLICATION SURFACES

Functional matt textured Betek Expert is applied after priming on interior old-new painted/plastered ceilings-walls, plaster, paste, plasterboard, concrete board, OSB, glass textile surfaces.

APPLICATION

Clean the application surface from any dirt, dust, mold oil, loose layers, and ensure the application surface is stable, dry, clean and self-supporting. Observe the setting period (28 days) on concrete, brute concrete, new plastered surfaces, and clean the loose plaster particles with scraper or similar methods. Correct and repair the surface if required. The substrate to be painted is critical for ensuring a high paint performance. Sand previously painted surfaces (water-solvent based) using a fine-grained emery paper, and then prime. Use Betek Primer or Betek Lux Primer on these surfaces or new plastered interior surfaces that will be treated for the first time. Absorbing and high dust generating surfaces like lime and whitewash must be completely removed and cleared away. Apply two coats of top coat paint after applying one coat of Betek Kapatan stain hiding paint and one coat of Betek Primer on very dirty surfaces in order to improve the covering strength of the paint. Betek Expert product must be applied in minimum 2 coats 24 hours after priming. Ensure that the ambient and surface temperatures are between +5°C and +30°C throughout the application and drying out period of the product. Apply to the entire wall from one corner to the other to ensure integrity on the surface. See attached technical documents for application guides on different surfaces, surface cleaning preparations and use of primer.

FOR AIRLESS SPRAYING

Pressure: 120-140 bars

Nozzle angle: 50°

Nozzle size (inches): 0,019"

Thinning: 10% (volume)

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com



THINNING

Recommended to be applied in minimum two coats on primer, according to the condition of the application surface and the color to be used, after thinning by maximum 25-30% by volume with clean water in brush and roller applications.

DRYING TIME (@ 20°C, 65% RH)

Touch dry: 30-60 minutes

Resting period between coats: 4-6 hours

Final Dry: 24 hours (drying time may increase at higher relative humidity and lower temperature)

CONSUMPTION

Depending on the type, absorbency and structure of the application surface, 14-18 m2 area can be painted in a single coat with 1 liter. Do a test run on a small area first to determine the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PROPERTIES

Provides functional results in both wall and ceiling applications. High retouching performance for its class. Painter-friendly. Spreads quickly on the surface and saves on labor, offers maximum covering area. Easy-to-apply, no splash/no drip formula. High coverage. Provides a breathable application surface. Integrates perfectly with the application surface. No cracking, blistering or flaking. Thinned with water, environmentally friendly. No disturbing odor during application.

PACKAGING

15 L, 7.5 L, 2.5 L

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com

