

DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK AQUALUX

PRODUCT DESCRIPTION

Betek AquaLux® is a water based, luxurious gloss textured, fully wipe-clean and washable, acrylic emulsion based, decorative top-coat paint developed for multi-purpose DIY use on different surfaces.

THINNING

The product is ready-to-use. Recommended to be applied in minimum two coats according to the applied surface's condition and color used after thinning by maximum 5% by volume with clean water in brush and roller applications.

DRYING TIME (@ 20°C, 65% RH)

Touch Dry: 30-60 minutes Resting period between coats: 4-6 hours

Final Dry: 24 hours, on furniture (tables, chairs, kitchen units and similar) 72 hours (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

Depending on the type, absorbency and structure of the application surface, an area of 13-20 m2 area can be painted in a single coat with 1 Liter. Perform a controlled sample run to estimate the precise consumption amount.

AIRLESS SPRAYING

Pressure: 120-140 bars

Nozzle angle: 50°

Nozzle size (Inch): 0.019"

Thinning: Ready to use.

Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 5% with clean water in airless spraying if needed.

PACKAGING

15 L, 2.5 L, 0.75 L

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

SPECIFICATIONS

Offers water-based luxurious glossy texture and superior whiteness for your walls. Fully wipe-clean and washable. Developed exclusively for the decoration and coloring of diverse surfaces such as wood, metal, glass, plastic, ceramic, fabric and wallpaper. Provides saving from labor thanks to its easy-to-spread texture. High hiding power. Integrates with the application surface. No cracking, blistering or flaking. No disturbing odor due its water-based formula and environment. Environment- and people-friendly.

APPLICATION SURFACES

Betek AquaLux® offering a luxurious glossy texture is applied after suitable priming on interior old-new painted/plastered ceilings-walls, plaster, paste, plasterboard, concrete board, OSB, glass textile surfaces and paintable wallpapers. In order to get maximum performance and to achieve the unique texture and shine of Betek AquaLux®, it is recommended to be applied on surfaces prepared with surface leveling products such as sateen plaster or putty. *Can be applied on wood and metal (interior and exterior) surfaces, provided the indicated surface preparation is made during application.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com

APPLICATION

Clean the application surface from any dirt, dust, mold oil, loose layers, and ensure the application surface is stable, dry, clean and self-supporting. Observe the setting period (28 days) on concrete, brute concrete, new plastered surfaces, and clean the loose plaster particles with scraper or similar methods. Correct and repair the surface if required. The substrate to be painted is critical for ensuring a high paint performance. Prefer Betek Primer for recently plastered interior surfaces that will be treated for the first time and old painted solvent surfaces, and Betek Lux Primer for old water-based surfaces before the paint application. Apply Betek 1/7 - 1/10 Concentrated Primer (thinned 1/5) or Betek Gel Primer on absorbing and high dust generating surfaces like plaster and aerated concrete. Before applying on hard and glossy surfaces (hard kitchen unit coatings, lacquer paint, glass, hard pvc and similar) Betex Astarix must be applied. Apply one or two coats of top coat Betek AquaLux® after applying one coat or two coats, if required, of Kapatan stain hiding paint and one coat of Betek Primer on very dirty surfaces in order to improve the coverage strength. See attached technical documents for application guides on different surfaces, surface cleaning preparations and use of primer.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com