

CREATIVE EFFECT PRODUCT GROUP

BETEK ROYAL SATIN

PRODUCT DESCRIPTION

Decorative paint with pearl appearance and water based with acrylic resin basis.

APPLICATION SURFACES

Pasted surface is necessary for application of Betek Royal Satin. Coatings from old painted, glass textile, wallpaper surfaces should be removed if possible. Surface should be pasted with BETEK INTERIOR PASTE.

APPLICATION

All surfaces where Betek Royal Satin will be applied should be smooth, solid, dry and clean to carry paint. Surface should definitely be pasted with BETEK INTERIOR PASTE. Than Betek Royal Satin will be applied with a roll of fine feathered brush. After the first layer is dried second layer of Betek Royal Satin is applied to surface with a roll of fine feathered and while it is wet, pattern is given with a Betek Royal Satin Roll. Application should be made between + 10°C and +35°C. there can be color tone difference due to applications methods for colors requested outside Betek Royal Satin color chart. It is recommended to make sample works in such cases.

TECHNICAL PROPERTIES

Color: Can be selected from Betek Royal Satin color card.

Brightness: 60°:37± 5 gloss

Density:1,1 ± 0,05 g/ml

THINNING RATIO

Ready for usage. Never make thinning.

DRYING PERIOD (20°C, At %65 HR)

First drying: 45 min.

Last drying: 24 hours

CONSUMPTION

Depending on surface absorption 8-12 m² area can be painted with 1 L. for definite consumption controlled sampling painting should be made.

STORAGE

It can be preserved for three years in unpacked packing in cool and dry environment by protecting from sun light and freezing. Please close the lid of the pack after usage by not allowing air contact.

PACKAGING

2.5 L

Hazard-determining components of labelling:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H isothiazol-3-one [EC no. 220-239-6] (3:1) formaldehyde

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com