



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: BETEK ASTARIX PAINT

· Article number: 81510-EN-01

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A.Ş. Gebze Organize Sanayi Bölgesi Tambelaya Alam 2200, Sakak No. 220

Tembelova Alanı 3200. Sokak No:3206

Tel: 0 (262) 678 30 00 Gulay.Artiran@betek.com.tr

- Further information obtainable from: R&D department
- · 1.4 Emergency telephone number: 0090 262 678 30 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Repr. 1B H360D May damage the unborn child.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 1)

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2-butanone oxime

calcium bis(2-ethylhexanoate)

· Hazard statements

H350 May cause cancer.

H360D May damage the unborn child.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains 2-butanone oxime. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25-50%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
CAS: 12001-26-2	Mica	2.5-10%
	substance with a Community workplace exposure limit	
CAS: 7779-90-0	trizinc bis(orthophosphate)	2.5-10%
EINECS: 231-944-3	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 96-29-7	2-butanone oxime	<i>≤</i> 2.5%
EINECS: 202-496-6	♦ Acute Tox. 3, H301; ♦ Carc. 1B, H350; STOT SE 1, H370; STOT RE 2,	
	H373; 📀 Eye Dam. 1, H318; 🔨 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin	
	Sens. 1, H317; STOT SE 3, H336	
	ATE: LD50 oral: 100 mg/kg	
	LD50 dermal: 1,100 mg/kg	

(Contd. on page 3)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

	(Conto	l. of page 2)
CAS: 136-51-6	calcium bis(2-ethylhexanoate)	<i>≤</i> 2.5%
EINECS: 205-249-0	♦ Repr. 1B, H360D	
CAS: 22464-99-9	zirconium salt of 2- ethylhexanoic acid	<i>≤</i> 2.5%
	♦ Repr. 2, H361d	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep respiratory protective device available.

(Contd. on page 4)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

12001-26-2 Mica

OEL Long-term value: 3 mg/m³ respirable fraction

96-29-7 2-butanone oxime

OEL Short-term value: 33 mg/m³, 10 ppm Long-term value: 10 mg/m³, 3 ppm Sens

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 4)

· Eye/face protection Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 36 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, <2% aromatics)

· Flammability *Not applicable.*

· Lower and upper explosion limit

 $0.6\ Vol\ \%$ · Lower: 7 Vol % · Upper: 62 °C · Flash point: 240 °C · Auto-ignition temperature: · Decomposition temperature:

Not determined. $\cdot pH$ Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

· water: Fully miscible. · Partition coefficient n-octanol/water (log value) Not determined. 1 hPa

· Vapour pressure at 20 °C:

Density and/or relative density

1.33 g/cm³ · Density at 20 °C: · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and

environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Organic solvents: 0.2 % · VOC (EC) 0.23 % · Solids content: 38.4 %

· Change in condition

· Evaporation rate Not determined.

(Contd. on page 6)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 5)

Information with regard to physical hazard class	ses
· Explosives	void
· Flammable gases	void
· Aerosols	void
· Oxidising gases	void
· Gases under pressure	void
· Flammable liquids	void
· Flammable solids	void
· Self-reactive substances and mixtures	void
· Pyrophoric liquids	void
· Pyrophoric solids	void
· Self-heating substances and mixtures	void
· Substances and mixtures, which emit flammable	e gases
in contact with water	void
· Oxidising liquids	void
· Oxidising solids	void
· Organic peroxides	void
· Corrosive to metals	void
Desensitised explosives	void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity May cause cancer.
- · Reproductive toxicity May damage the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

IE

(Contd. on page 7)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
$\cdot ADR$	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (trizinc bis(orthophosphate))
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (trizinc bis(orthophosphate)), MARINE POLLUTANT
·IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
	N.O.S. (trizinc bis(orthophosphate))

- · 14.3 Transport hazard class(es)
- \cdot ADR



Class 9 (M6) Miscellaneous dangerous substances and articles.

(Contd. on page 8)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

	(Contd. of page
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
Special marking (ADK): Special marking (IATA):	Symbol (fish and tree)
<u> </u>	* * *
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Miscellaneous dangerous substances and articles. 90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IM instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
To a second second second	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 (-)
	17
IMDG	5 <i>L</i> .
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
Excepten quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per timer packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (TRIZINC BIS(ORTHOPHOSPHATE)), 9, 1.

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)

according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 8)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Class	Share in %
Ι	0.9

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H360D May damage the unborn child.
- H361d Suspected of damaging the unborn child.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

(Contd. on page 10)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date: 28.11.2024 Version number 1 Revision: 28.11.2024

Trade name: BETEK ASTARIX PAINT

(Contd. of page 9)

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1B: Carcinogenicity – Category 1B Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

IE