

GLUE & ADHESIVE PRODUCT GROUP

BETEK PVA GLUE

DESCRIPTION

54% solid polyvinyl acetate-based white glue with filler that is stabilized with polyvinyl alcohol and surfactant

SPECIFICATIONS

Appearance	White
Solid Ratio (%)*	54 ± 2
pH	7,0 ± 1,0
Viscosity (mPa.s)**	12500 ± 2500
Density (g/cm ³)	1.25 ± 0.02
MFFT	5 ± 1

*3 hours in 110°C-115°C

**Brookfield LVDV-II +, 20°C, Spindle 3/20 rpm

APPLICATION SURFACES

Can be used safely in coating, fixing and backing all types of wood, chipboard, MDF.

APPLICATION

- Clean all types of dust, oil and dirt on the application surface.
- Ensure the surface temperature and the ambient temperature are above **+5°C** during application.
- Apply the glue in an amount that overflows from the edges of the application surface and wipe the overflowing product with a damp cloth.
- Fix after waiting maximum 10 minutes.
- The product is ready-to-use. Do not add any water.
- Close the lid of the package firmly after the application.
- Applied with brush or roller.
- After application, all used tools should be cleaned with water.
- Avoid using any rusty tool.

DRYING TIME (at 20°C, 65% HR)

Varies between 0.5 to 2 hours depending on the thickness of the applied film, the type of the application surface, the temperature and the humidity of the environment.

CONSUMPTION

150-250 g/m² depending on the thickness of the applied film and the application surface.

FLASH POINT

<40°C

STORAGE

Can be stored for 1 year provided that its package is unopened and it is in a 0-40°C place away from sunlight. Protect from frost.

PACKAGING

28 Kg, 10 Kg, 3 Kg, 0.85 Kg

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com

HAZARD STATEMENTS

H317 May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com