



MULTI-PURPOSE RENOVATION PAINT

AQUA RENO® UNIVERSAL

PRODUCT DESCRIPTION

Aqua Reno® Universal is a multi-purpose renovation paint developed for home improvement ideas, with a silky glossy finish, fully wipeable and washable properties, acrylic-based, water-based, and featuring self-catalyzed (Self Catalyzed) technology.

Thanks to its Self Catalyzed Polymer technology, the paint provides excellent adhesion and excellent spreading on the applied surface without requiring any catalyst or priming process.

The innovative double effect of the self-catalyzed polymer enables effortless application while also providing excellent adhesion to many difficult surfaces such as tiles, ceramic tiles, kitchen countertops, bathroom furniture, metal, marble, glass, and plastic.

FEATURES

- Can be effortlessly applied by people painting for the first time.
- Ready to use. Stir gently before application.
- Does not require a catalyst.
- Features Self Catalyzed (Self-Catalyzed) Polymer technology.
- Does not require primer.
- Provides excellent spreading during application and excellent adhesion (bonding) on the surface.
- Has a maximum hiding structure.
- Has a Toy Safety Certificate (EN 71-3). Thanks to this, it can also be safely used on surfaces that children come into contact with.
- Offers Superior Heat Resistance, Superior Impact Resistance, and Superior Resistance to Household Cleaners.
- Fully wipeable and washable.
- Thanks to its high resistance against challenging effects such as water, moisture, and steam, it has been developed for kitchen and bathroom surfaces (countertops, tiles, ceramic tiles, kitchen and bathroom cabinets, shower enclosures, white goods, etc.).
- Offers maximum resistance against potential and difficult contaminants encountered in the kitchen, such as oil, tomato paste, and ketchup. It also provides excellent protection against very difficult contaminants such as tea and coffee with the application of Aqua Reno Varnish.
- Thanks to its smooth structure, it is suitable for painting white goods.
- Surfaces can be put into use 1 day after application. For detailed information, please see the “Drying Times” section.
- Has 1000+ color alternatives developed with Betek’s color expertise.

APPLICATION SURFACES

It can be applied to surfaces such as tiles, floor tiles, kitchen countertops (granite, marble, wood, quartz, etc.), kitchen cabinets, raw wood, lacquered surfaces, inox kitchen surfaces, panel doors, glass, parquet, PVC, windows, bathroom cabinets, washing and drying machine surfaces, PVC/acrylic glass/glass shower enclosure surfaces.

Note: It is not suitable for use on wall and ceiling surfaces or exterior facades.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com





APPLICATION

First, the surface must be cleaned and freed from dust, oil, all kinds of rust, and dirt. For surface cleaning, especially on surfaces where soap and detergent residues are frequently encountered, the surfaces should be cleaned with white vinegar diluted 1:1 with water. The product has a wide variety of application areas. All surfaces to which the product can be applied must be lightly sanded before application, and the dust should be removed with a damp cloth after the process.

After the cleaning process, the surfaces should be lightly sanded with No. 240/280 sandpaper and, after removing the dust, Aqua Reno® Universal should be applied. For higher performance on horizontal surfaces, Aqua Reno® Varnish should be applied. On surfaces where Aqua Reno® Varnish has been applied, kettle marks do not form, stains can be removed from the surface very easily, and scratch resistance reaches its maximum level. Aqua Reno® Varnish application is recommended to increase surface performance on bathroom and kitchen cabinet surfaces due to moisture, steam, and cleaning requirements that may occur.

Primer application is not required before application.

Application Tools: Aqua Reno® Universal is recommended to be applied in at least two coats using a velvet roller and Floor Brush.

THINNING

The product is ready to use.

DRYING TIME

At 20°C and 65% relative humidity;

Touch Dry: 30 minutes

Application Between Coats: 30–60 minutes

Opening the Space for Use: 24 hours

Aqua Reno® Varnish can be applied over Aqua Reno® Universal 4 hours after the final coat of paint application. During detailed cleaning (household cleaners, etc.) within the first seven days, it is recommended to proceed carefully. The product reaches maximum performance after 21 days. Drying time may be extended at higher relative humidity and lower temperatures.

COVERAGE

Coverage varies depending on the type, absorbency, structure of the surface to be applied, and application habits. At least two coats are recommended.

MDF Lam Bathroom and Kitchen Cabinets: 10–14 m²/L per coat

Tile and Ceramic Tile Surfaces: 14–18 m²/L per coat

White Goods Surfaces: 17–21 m²/L per coat

PVC/Acrylic Glass/Glass Shower Enclosure Surfaces: 17–21 m²/L per coat

Kitchen Countertops: 20–24 m²/L per coat

INOX Surfaces: 17–21 m²/L per coat

A controlled sample application should be carried out for exact coverage.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com





STORAGE

Shelf Life: Can be stored for 3 years in its unopened packaging in a cool and dry place, protected from frost and direct sunlight. Close the lid of the package immediately after use in a way that prevents air from entering.

PACKAGING

2,5 L ; 0,75 L

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No: 38 34852 Maltepe, İstanbul / Türkiye
Tel: +90 (216) 571 11 00 - Faks: +90 (216) 571 13 70 - www.betekexport.com

