

Front Adjustable Track Bar

Dodge Ram | 2013-2020 3500 4WD Pickup | 2014-2023 2500 4WD Pickup

Part #: 122324

Rev. 080524



491 W. Garfield Ave., Coldwater, MI 49036 • Phone: 517-279-2135

Web: www.bds-suspension.com • E-mail: tech-bds@ridefox.com

SAFETY WARNING

BDS Suspension Co. recommends this system be installed by a professional technician. In addition to these instructions, professional knowledge of disassembly/ reassembly procedures and post installation checks must be known.

INSTALLATION INSTRUCTIONS

1. Park vehicle on clean flat and level surface. Block the rear wheels for safety.
2. Remove the factory trackbar, retain hardware for installation of new trackbar.
3. Adjust trackbar length to stock length for stock height applications and lifts with track bar bracket, adjust to 39-1/8" for 3" of lift.
4. Install trackbar with the gussets on the 'bottom' side with factory hardware, apply thread locker to the threads.
5. Adjust length of trackbar to center axle.
6. Tighten trackbar axle hardware to 285 ft-lbs and frame hardware to 74 ft-lbs plus 160deg of rotation
7. Remove the 4 allen bolts and apply thread locker to the threads, reinstall into trackbar.
8. First, tighten pinch bolts on trackbar left-to-right at 30 ft-lbs.
9. Repeat left-to-right torque sequence at 30 ft-lbs until all pinch bolts meet 30 ft-lbs specification.
10. Adjust drag link length to get the steering wheel to be centered. Ensure there is proper engagement of threads. Do not drive the vehicle for extended periods of time with the steering wheel crooked.
11. Recheck all hardware, check again at regular maintenance intervals.

Bill of Materials

Part #	Qty	Description
A432	1	Adjustable Track Bar Assembly
342701	1	Thread Locker

