



REV	DESCRIPTION	DATE
△	RDK-98020	謝婉如 2009/09/01
△	B210-規範-91018	謝婉如 2009/09/02
△	RDC-99171	謝婉如 2010/06/15
△	PPAP-109670	林淑楨 2020/11/03

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :  $\frac{\text{A.W.G.} | 4 |}{\text{AMP.} | 125 |}$
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : NYLON
  4. INSULATION COLOR : YELLOW
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 4 A.W.G. ( 22 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 1.7 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	NYLON-INSULATED RING TERMINALS	UNIT	mm	⊕	□
PART NO.	RNYB22-10	MATERIAL	-----	APPROVE	張馨尹
NUMBER	KA-94143-C	SCALE	REV.	SHEET	CHECKED 柯輝強
DATE	2006/05/29	2/1	1-5	10F1	DRAWN 張馨尹

**KST** K.S. TERMINALS INC.