



| REV | DESCRIPTION | DATE |
|-----|---------------|----------------|
| △ | RDK-98020 | 謝婉如 2009/09/01 |
| △ | B210-規範-91018 | 謝婉如 2009/09/02 |
| △ | RDC-99171 | 謝婉如 2010/06/15 |

- NOTE :
- MAXIMUM ELECTRIC CURRENT :

| | | | |
|--------|-----|--|--|
| A.W.G. | 4 | | |
| AMP. | 125 | | |
 - MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 - INSULATION MATERIAL : NYLON
 - INSULATION COLOR : YELLOW
 - TERMINAL MATERIAL : COPPER
 - WIRE RANGE : 4 A.W.G. (22 mm^2)
 - TERMINAL SURFACE TREATMENT : TIN PLATED
 - TERMINAL THICKNESS : 1.7 mm

| | |
|--|--------------|
| △ Tolerance Unless Otherwise Specified | |
| 0 > mm ± | ANGLE |
| > mm ± | 0° > ° REF ± |
| > mm ± | ° ° ± |
| > mm ± | ° ° ± |

| | | | | | | |
|----------|--------------------------------|----------|-------|---------|---------|-----|
| NAME | NYLON-INSULATED RING TERMINALS | | | UNIT | mm | |
| PART NO. | RNYB22-11 | MATERIAL | ----- | APPROVE | | |
| NUMBER | KA-95387-C | SCALE | SHEET | PAGE | CHECKED | |
| DATE | 2006/05/29 | 2/1 | 1-4 | 10F2 | DRAWN | 張馨尹 |

KST. K.S. TERMINALS INC.