



| REV | DESCRIPTION | DATE |
|-----|-------------|----------------|
| △ | RDCM-107002 | 林淑禎 2018/04/20 |

- NOTE :
- MAXIMUM ELECTRIC CURRENT : $\frac{MCM}{\Delta AMP.} \left| \frac{400}{545} \right|$
 - WIRE RANGE : 400 MCM (240 mm²)
 - SURFACE TREATMENT : TIN PLATED
 - THICKNESS : 2.75 mm

| Tolerance Unless Otherwise Specified | |
|--------------------------------------|----------|
| 0 > 6 mm ± 0.20 | ANGLE |
| 6 > 18 mm ± 0.30 | 0° REF ± |
| 18 > 30 mm ± 0.40 | ° ± |
| 30 > 75 mm ± 0.50 | ° ± |

| | | | | | | |
|----------|--|----------|----------------|---------|---------|-----|
| NAME | NON-INSULATED COPPER TUBULAR LUGS(TL SERIES) | | | UNIT | mm | |
| PART NO. | TL240-14 | MATERIAL | COPPER TUBULAR | APPROVE | | |
| NUMBER | KT-970058-C | SCALE | REV. | SHEET | CHECKED | |
| DATE | 2008/05/07 | 1/1 | 1-1 | 10F1 | DRAWN | 張馨尹 |

KST. K.S. TERMINALS INC.