



| REV | DESCRIPTION | DATE           |
|-----|-------------|----------------|
| △   | RDK-97163   | 張馨尹 2008/08/26 |
| △   | PPAP-109359 | 林淑禎 2020/06/17 |
| △   | RDK-109028  | 林淑禎 2020/07/23 |
| △   | RDK-109050  | 郭碧紋 2022/11/17 |

- NOTE:
1. MAXIMUM ELECTRIC CURRENT : 

|        |    |
|--------|----|
| A.W.G. | 20 |
| AMP.   | 12 |
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : NYLON
  4. INSULATION COLOR :  
 FRENCH COLOR : WHITE  
 GERMAN COLOR : ORANGE  
 DIN COLOR : WHITE
  5. CONNECTOR MATERIAL : COPPER TUBE.
  6. WIRE RANGE : 20 A.W.G.( 0.50 mm<sup>2</sup>)
  7. CONNECTOR SURFACE TREATMENT : TIN PLATED
  8. ( △ ) : MEAN REFERENCE.

| Tolerance Unless Otherwise Specified |                 |
|--------------------------------------|-----------------|
| 0 >                                  | mm ± 0.50 ANGLE |
| >                                    | mm ± 0° REF ±   |
| >                                    | mm ± ° ±        |
| >                                    | mm ± ° ±        |

|          |                                               |          |       |         |         |     |  |
|----------|-----------------------------------------------|----------|-------|---------|---------|-----|--|
| NAME     | NYLON-INSULATED CORD END TERMINALS (F SERIES) |          |       |         | UNIT    | mm  |  |
| PART NO. | E0505                                         | MATERIAL | ----- | APPROVE |         |     |  |
| NUMBER   | KA-95405-C                                    | SCALE    | REV.  | SHEET   | CHECKED |     |  |
| DATE     | 2006/05/10                                    | 5/1      | 1-4   | 10F1    | DRAWN   | 張馨尹 |  |

**KST. K.S. TERMINALS INC.**