



HIGH CUT LEVEL, ULTRA DEXTERITY IMPACT GLOVE

Ultra dexterity impact glove with a high level of cut protection so you can focus on work, not your gloves.

FEATURES

- > Cut resistance: level F (EN388:2016) / ANSI A6
- > Water repellent thin synthetic leather palm with high cut resistance fabric on palm feel like a classic mechanic's glove
- Dense, moulded TPR protection zones on knuckles, fingers, thumb and back of hand.
- Ergonomically designed TPR follow the hand movement reducing hand fatigue
- Ergonomically curved fingers to reduce hand fatigue
- > Reinforced thumb crotch/saddle to prolong wear
- > Adjustable cuff with elastic for a custom fit
- > ANSI Level 2 impact protection
- 360 degree water repellent treatment to keep your hands dry







SUITABLE FOR

Typical Industries

- Oil and Gas
- Construction
- Mining
- Transport
- Heavy Engineering
- Offshore
- Ports

Suitable Applications

- Demolition
- Drilling
- Extraction
- Heavy handling
- Cargo handling
- Extraction and refining
- Rigging

CERTIFICATION









See overleaf for explanation







△SKYTEC Torq Strike EC[™]

PRODUCTION INFORMATION

MATERIALC	LINER:	Foam laminated spandex fabric	
MATERIALS	COATING:	Synthetic leather and knitted cut resistant fabric	
COLOUR	Red/Yellow		
LENGTH (mm)	250 (Size Dependent)		
CUFF STYLE	Elasticated knit wrist with open cuff		

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M 9/L 10/XL 11/XXL 12/XXXL 13/XXXXL	SKG00054EF SKG00054EH SKG00054EJ SKG00054EL SKG00054EN SKG00054EP	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE


- USE: General handling glove with cut and impact protection. Not suitable for high thermal (beyond 100°C/212°F), electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement $% \left(1\right) =\left(1\right) \left(1\right)$
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS





EN 407



CLASSIFICATION FOR CUT RESISTANCE					
Measured breakthrough time	Permeation performance index (grams)				
A1	≥ 200				
A2	≥ 500				
A3	≥ 1000				
A4	≥ 1500				
A5	≥ 2200				
A6	≥ 3000				
A7	≥ 4000				
A8	≥ 5000				
A9	> 6000				

	Puncture Resistance (newtons)				
1	10-19				
2	20-59				
3	60-99				
4	100-149				
5	150+				
Puncture Resistance (ANSI/ISEA 105): Puncture resistance is determined by the max for that it takes, exerted from a probe, to puncture the fabric.					

ANSI/ISEA 105-2016 ABRASION RATING CHART							
Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

CLASSIFICATION FOR IMPACT RESISTANCE				
Performance level				
1	≤ 9	< 11.3		
2	≤ 6.5	≤ 8.1		
3	≤ 4	≤ 5		

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M171SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-TORQ-STRIKE-EC-1023_1

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575) UKCA compliance certificate delivered by the notified body ITS Testing Services UK Ltd, Centre Court, Mendian Business Park, Leicester, LE19 1WD, United Kingdom (Approved Body No. 0362)