



S-TEX 377SC

CUT PROTECTION WITH GAUNTLET SAFETY CUFF

Double-dipped, fully coated nitrile with extra nitrile foam coating on palm over Hagane Coil® liner (stainless steel/polyester), and PVC/polyester safety cuff. Safety cuff provides protection over the wrist as well as easy donning and doffing.

FEATURES

- > Cut resistant: Level D (EN 388:2016)
- ▶ 13 gauge knitted liner, engineered with Hagane Coil® technology
- > Strong, sturdy cuff extends protection to over this wrist
- Safety cuff enables quick and easy removal in case of emergency
- Nitrile coating with a second foamed nitrile coating provides high abrasion resistance
- Protects the hand from oils, hydrocarbons, grease and abrasion, with long lasting grip performance under wet and oily conditions
- An ergonomically designed hand mould replicates the natural curvature of the human hand to reduce hand fatigue, increasing productivity and dexterity
- > Seamless knitting gives no irritation
- > Liquid-proof to end of coated area
- Optimal grip performance in wet & oily conditions















SUITABLE FOR

Typical Industries

- Agriculture
- Construction
- Glass
- Mining
- Oil and Gas

Suitable Applications

- Drainage
- Glass and window handling
- Plumbing
- Steel erecting
- Bottling
- Heavy equipment handling

CERTIFICATION

CAT II



4X41D

EN 388:2016

EN 407:2004



X1XXXX

See overleaf for explanation







⊔⊢. S-TEX 377SC

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge Hagane Coil® (Stainless steel/polyester)
	COATING:	Foam nitrile over nitrile. Polyester / PVC safety cuff
COLOUR	Blue/black	
LENGTH (mm)	300 (size dependent)	
CUFF STYLE	Safety cuff	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/M 8/L 9/XL 10/XXL	SHOS377C2 SHOS377C3 SHOS377C4 SHOS377C5	5 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: Cut resistant glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use


CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



HEAT AND FIRE EN 407



EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-S-TEC 377SC_0620_1