

HIGH CUT RESISTANT PU COATED GLOVE WITH RECYCLED POLYESTER

Dexterous high cut resistant PU palm coated glove with 25% rPET, glass and steel fibre free, touchscreen and reinforced on the thumb crotch.

FEATURES

- › High cut resistance: Level E (EN 388:2016) / ANSI A5
- › 15 gauge engineered HPPE with recycled polyester (25% of liner content) offers a unique sensation of comfort and protection
- › Steel and glass fibre free to avoid any risks of irritation
- › Durable PU palm coating ensures good protection against abrasion and secure grip in dry and greasy conditions
- › Reinforced thumb crotch enhances durability
- › Touchscreen capabilities to allow usage with screen devices
- › Seamless knit prevents irritation
- › RCS (Recycled Claim Standard) certified
- › 1 pair = 1PET bottle of 500ml recycled
- › 18g of CO₂ reduced vs virgin polyester alternative



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Metal Industry

Suitable Applications

- Assembling
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics
- Metal Stamping

CERTIFICATION



See overleaf for explanation



Eco Rhodium™

PRODUCTION INFORMATION

MATERIALS	LINER:	15 gauge engineered HPPE, recycled polyester (25%)
	COATING:	Polyurethane (PU)
COLOUR	Grey/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00049BB	10 pairs per paper wrap
7/S	SKG00049BD	
8/M	SKG00049BF	
9/L	SKG00049BH	
10/XL	SKG00049BJ	120 pairs per case
11/XXL	SKG00049BL	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)
 UKCA Type-Examination Certificate issued by CCQS UK Ltd, 25 Wilton Rd, Pimlico, London SW1V 1LW, United Kingdom. [UK Approved Body No. 1105].

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.