STINGER®

Rugged safety glasses with well-placed ventilation and maximum side coverage for demanding environments

The Stinger® safety glasses are built for demanding work environments where durability, coverage, and comfort are essential. Featuring a rugged frame design and a single 9-base curve lens, they deliver superior side protection, excellent peripheral visibility, and dependable impact resistance. Strategically placed ventilation ports help improve airflow, while soft TPR nose pieces and rigid flared temple ends provide a secure, slip-resistant fit. Designed for tough industrial conditions, the Stinger offers the performance and comfort needed for all-day wear.

LENS OPTION

- Yellow







FEATURES

- Rugged frame design delivers enhanced durability, standing up to the demands of tough industrial work environments
- Single 9-base curve lens provides superior side coverage, helping protect against hazards from multiple angles
- Wraparound lens design enhances peripheral awareness, improving visibility
- Rigid, flared TPR temple ends create a secure, stable fit, helping keep eyewear comfortably in place during active work
- Soft TPR nose pieces help prevent slipping, providing added comfort and stability throughout the workday
- Strategically placed ventilation ports promote airflow, helping reduce heat buildup and improve wearer comfort
- Designed for maximum impact resistance, offering dependable protection in high-exposure industrial applications
- Combines rugged performance with all-day wearability

Z87+ ANSI/ISEA Z87+ HIGH MASS IMPACT

ANTI-FOG ANTI-FOG LENS COATING

UV PROTECTION UV PROTECTION

HARD COAT HARD COAT

FLAME RESISTANT FOAM FLAME RESISTANT FOAM

13915 Radium St NW
Ramsy, MN 55303

763-450-0110
Sales@BullheadSafety.com

GlobalGlove.com
BullheadSafety.com

BULLHEAD SAFETY® EYE PROTECTION

Bullhead Safety® EYEWEAR

STINGER®

ITEM	LENS COLOR	FEATURES	COATING	FRAME COLOR	ITEMS PER PACK	ITEMS PER CASE
BH61084AF	Yellow	Ballistic Rated, Tapered Lens, UV Protection	Anti-Fog, HC**	Woodland Camo	12 x Pack of 12	144 x Pack of 12

**Hard Coat

SPECIFICATIONS

TAPERED LENS	Yes
UV	U6
IMPACT RATING	Z87+
FRAME TYPE	Half Frame
FRAME WIDTH	142 mm
BASE CURVE	9

PACKAGING

	EACH	INNER PACK	CASE
DIMENSIONS	6 × 3 × 2 in	11 × 7 × 5 in	27 × 12 × 14 in
WEIGHT		2 lb	15 lb
UPC/GTIN	81029202151	10810292021518	20810292021515

ADDITIONAL INFORMATION

CERTIFICATION LEGEND

or click here

VIEW PRODUCT ONLINE

or click here

13915 Radium St NW
Ramsy, MN 55303

763-450-0110
Sales@BullheadSafety.com

GlobalGlove.com
BullheadSafety.com

GGS