

Benchmark**BMG215**

SOFT AND DURABLE NITRILE FOAM COATED GLOVE

Lightweight general handling glove reinforced at the thumb crotch. Outstanding durability and grip properties.

FEATURES

- › Seamless nylon/spandex liner provides superior comfort and dexterity
- › Thin and robust nitrile foam coating enhances fingertip sensitivity
- › Excellent grip in both wet and dry environments
- › Anatomically designed for maximum fit
- › Reinforced thumb crotch increases durability
- › An Oeko-Tex™ certified product
- › Breathable back of hand to reduce perspiration
- › Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Automotive
- Automotive
- Logistics
- Maintenance
- Manufacturing
- Oil and Gas
- Utilities

Suitable Applications

- Assembly
- Assembly
- Goods Handling
- Light Fabrication
- Quality Inspection
- Warehousing

CERTIFICATION

EN 388:2016



4131X

See overleaf for explanation

Benchmark**BMG215****PRODUCT INFORMATION**

MATERIALS	LINER:	15 gauge nylon, spandex
	COATING:	Foam nitrile
COLOUR	Grey / Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	BMG00215FB	10 pairs per bag 120 pairs per case
7/S	BMG00215FD	
8/M	BMG00215FF	
9/L	BMG00215FH	
10/XL	BMG00215FJ	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)
				Impact Resistance	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globus.co.uk

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | BMK-DATA-BMG215-0321_1