Benchmark

BMG460



SINGLE-USE POWDER FREE NITRILE GLOVE

Lightweight, powder-free, single-use gloves with textured fingertips. Provides a very good alternative to Vinyl gloves.

FEATURES

- > Textured finish on the fingertips to enhance grip
- > Comfortable with a 'second skin' feel
- > Latex and powder-free
- Approved for food handling
- > Beaded cuff
- > AQL 1.5
- > Dual labelling: PPE and medical
- Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)
- > Thickness: 0.07mm, weight: 3.5gr



SUITABLE FOR

Typical Industries

- Aerospace
- ChemicalElectronics
- Food
- Pharmaceutical
- Manufacturing
- Oil and Gas

Suitable Applications

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION



See overleaf for explanation



Benchmark

BMG460



PRODUCT INFORMATION

MATERIAL	Nitrile
COLOUR	Blue
LENGTH (mm)	240
CUFF STYLE	Beaded

ORDERING DETAILS

SIZE	ITEM NO.	PACKAGING
6½-7 / S 7½-8 / M 8½-9 / L 9½-10 / XL 10½-11 XXL	BMG00460DD BMG00460DF BMG00460DH BMG00460DJ BMG00460DL	Boxes of 100 pcs, 10 boxes per case

RECOMMENDATIONS FOR USE

USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.

STORAGE: Store in dry conditions in the original packaging and away from direct sunlight.

CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.

LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

CERTIFICATION LEGENDS

	_
1,2	
1 11	
	/
	/

С

E

F

G

н

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374: 2016

CODE CHEMICAL CODE CHEMICAL Methanol n-Heptane A B Acetone Κ Sodium hydroxide 40 Acetonitrile Sulphuric acid 96% Dichloromethane M Carbon Disulfide N 65% Nitric acid 99% Acetic acid D Toluene 0 25% Ammonium hyd 30% Hydrogen perox

P Diethylamine Tetrahydrofurane S Ethyl acetate T

Ethyl acetate

EN455-1:	Freedom from holes	
EN455-2:	Physical properties	
EN455-3:	Biological evaluation	
EN455-4:	Shelf Life	

CHEMICAL n-Heptane Sodium hydroxide 40%	TYPE OF GLOVES	BREAKTHROUGH TIME
Sulphuric acid 96% 65% Nitric acid	А	≥30 min for at least 6 chemicals
99% Acetic acid 25% Ammonium hydroxide	В	≥30 min for at least 3 chemicals
30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	С	≥10 min for at least 1 chemical
or for onnaidonydo		

FOOD CONTACT DIRECTIVE EC 10/2011

 \mathfrak{B}

EUROPE

www.globus.co.uk

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +971 4 882 9962
- F: +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



© 2021Globus (Shetland) Ltd | BMK-DATA-BMG460-0222 1

EC compliance certificate delivered by the notified body, CTC, 4, rue Hermann Frenkel, 69367 Lyon Cedex 07, France (Notified Body No. 0075)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary