Benchmark

BMG788



CUT E HPPE, STEEL, NYLON/NITRILE FOAM GLOVE

Extremely flexible and dexterous, yet provides outstanding cut resistance for protection in high cut risk applications. Ideal in dry, greasy or oily conditions.

FEATURES

- > Excellent cut resistance: Level E (EN 388:2016)
- Steel Fibre within the liner provides a high level of cut protection for use in high cut risk environments
- > HPPE inner liner improves comfort and keeps the hand fresh
- Nitrile Foam palm provides a secure grip in light oily, greasy or dry conditions
- > Reinforced thumb crotch helps extend the gloves wearable life
- > Designed for easy movement and continuous wearing
- > Breathable on the back of hand to reduce perspiration
- > Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Aerospace
- Construction
- Glass
- Highways
- Rail
- Recycling
- Waste Management

Suitable Applications

- Cargo Handling
- FOD Reduction
- Hand Signalling
- Handling Materials with Sharp Edges
- Heavy Cutting
- Lineside Maintenance
- Repair and Maintenance

EN 388:2016 EN 388:2016 4X43E

See overleaf for explanation



Benchmark

BMG788



PRODUCT INFORMATION

MATERIALS	LINER:	HPPE/ Steel fibre / Nylon	
	COATING:	Nitrile foam	
COLOUR	Grey / Black		
LENGTH (mm)	230-270 (Size Dependent)		
CUFF STYLE	Elasticated, Knit wrist		


ORDERING DETAILS

SIZE	ITEM NO.	PACKAGING
7/S 8/M 9/L 10/XL	BMG00788FD BMG00788FF BMG00788FH BMG00788FJ	Individually bagged 10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- It is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use.
- Do not use near moving machines if there is a risk of entanglement.
- Storage: Gloves should be ideally stored in cool, dry conditions in original packaging and away from direct sunlight.
- Cleaning/Maintenance: Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Don't use chlorine bleaches.

CERTIFICATION LEGENDS



EUROPE

www.globus.co.uk

E: sales@globus.co.uk **T:** +44 (0)161 877 4747 **F:** +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962

F: +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2019 Globus (Shetland) Ltd | BMK-DATA-BMG788-1119 1