



BULLHEAD SAFETY® HEARING PROTECTION

Corded Polyurethane Foam NRR 32 dB Earplugs

Description

These single-use foam earplugs provide simple, effective protection against hearing damage by greatly reducing environmental noise. Highly visible orange and shaped to conform to the ear canal, the soft, slow-recovery foam is rated for a protection level of NRR 32 dB.

Each pair is individually packaged in a polybag for retail sale.

INDUSTRY

Airport Crews	Waste Management
Construction	Transportation
Automotive	Manufacturing
Printing	Utility Work



Features

- Single-use disposable earplugs
- 100% PVC-free polyurethane foam
- Extra-soft, lightweight foam seals the ear canal without pressure
- Bullet shaped provides a snug fit while gently conforming to the ear canal
- Expandable, slow rebound foam provides the best combination of comfort and protection for most users
- Made of soft non-allergenic material

ITEM **HP-F2** NRR **32 DB**



Specifications

MATERIAL	COLOR	SHAPE	CORDED	METAL DETECTABLE	POLY BAGGED	RETAIL READY	PAIRS/BOX
PVC-Free Polyurethane Foam	High-Visibility Orange	Bullet	Yes	No	Individual Pairs	Yes	100
ANSI S3.19-1974 NRR RATING		EN 352-2: 2002 SNR RATING					
32 dB		39 dB					

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (DB)	32.7	39.0	47.0	42.7	39.8	43.6	45.1	48.3	47.9	32 dB
STANDARD DEVIATION (DB)	5.4	5.4	5.2	4.7	3.6	4.9	3.0	3.2	3.3	
ASSUMED PROTECTION (DB)	21.9	28.2	36.6	33.3	32.6	33.8	39.1	41.9	41.3	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	4000	8000	8000
SOUND ATTENUATION (DB)	32.7	39.0	47.0	42.7	39.8	45.1	47.9	46.1
STANDARD DEVIATION (DB)	5.4	5.4	5.2	4.7	3.6	3.0	3.3	5.9
ASSUMED PROTECTION (DB)	27.3	33.6	41.8	38.0	36.2	42.1	44.6	40.2
SNR = 39 dB		H = 37 dB	M = 38 dB	L = 35 dB				

Packaging

	QUANTITY	HP-F2
EACH PAIR	1	810292029517
INNER BOX	100 PAIRS/PACK	10810292029514
CASE	10 PK/CASE	20810292029511
CASE WEIGHT (IN POUNDS)	12	

