знаша. 727

UNLINED, NITRILE GAUNTLET WITH CHEMICAL RESISTANCE

Made from a special SHOWA nitrile compound, the SHOWA 727 is a lightweight unsupported, gauntlet that's resistant to a range of solvents, animal fats and other chemicals.

FEATURES

- > 100% nitrile
- A bisque finish allows secure handling in wet and dry conditions
- Nitrile protects from oils, hydrocarbons and grease penetration
- > Embossed with the size for ease of pairing after laundering
- > Wrist well protected
- > Length: 33cm
- > Thickness: 0.38mm
- > Flock-lined version available: SHOWA 730
- > Chlorinated







SUITABLE FOR

Typical Industries

- Agriculture
- Chemical
- Automotive
- Contract cleaning
- Municipal Services
- Oil and Gas



- Cleaning
- Chemical Handling
- Degreasing
- Maintenance
- Refining
- Tank Filling

CERTIFICATION



See overleaf for explanation






PRODUCT INFORMATION

MATERIALS	LINER:	Unsupported, unlined
	COATING:	Nitrile
COLOUR	Green	
LENGTH (mm)	330	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING	VEND COMPA	TIBLE OPTION
7/S	BST727G1	12 pairs	BSTV727G1	144
8/M	BST727G2	per bag	BSTV727G2	individually
9/L	BST727G3	144 pairs	BSTV727G3	bagged pairs
10/XL	BST727G4	per case	BSTV727G4	per case

CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

L-

ESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

RESISTA	NCE TO CHEMI	CAI
CODE	CHEMICAL	COD
Ą	Methanol	J
В	Acetone	К
C D	Acetonitrile	L
	Dichloromethane	Μ
E F G	Carbon Disulfide	Ν
F	Toluene	0
G	Diethylamine	Ρ
н	Tetrahydrofurane	S
	Ethyl acetate	Т

CHEMICAL n-Heptane	TYPE OF GLOVES	BREAKTHROUGH TIME
Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid	А	≥30 min for at least 6 chemicals
99% Acetic acid 25% Ammonium hydroxide	В	≥30 min for at least 3 chemicals
30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	С	≥10 min for at least 1 chemical

RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

B

FOOD CONTACT DIRECTIVE EC 10/2011

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- +44 (0)161 877 4747 T:
- +44 (0)161 877 4746 F:

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- +971 4 882 9962 T:
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2021 Globus (Shetland) Ltd | SHO-DATA-727_0621_1

EU compliance certificate delivered by the notified body SATRA Technology Europe, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (NB 2777) The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.