

CUT AND HEAT RESISTANT

Knitted liner made with HPPE, spandex and engineered cut resistant fibres to provide a high cut resistance barrier, while offering dexterity and comfort.

FEATURES

- › Cut resistant: Level D (EN 388:2016)
- › HPPE, spandex and engineered cut resistant fibres provides good flexibility and comfort
- › Zorb-It® nitrile coating gives exceptional grip while allowing breathability, keeping your hands dry and comfortable
- › Light contact heat protection up to 250°C
- › Designed for easy movement and continuous wear
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure and comfortable fit
- › Food safe approved



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Maintenance
- Manufacturing
- Municipal Services

Suitable Applications

- Assembly
- Handling sharp and oily parts
- Machining

CERTIFICATION

CAT II



EN 388:2016



4X42D

EN 407:2004



X2XXXX



See overleaf for explanation

PRODUCT INFORMATION		
MATERIALS	LINER:	13 gauge HPPE, engineered cut resistant fibres, spandex
	COATING:	Zorb-It® Nitrile
COLOUR	Grey/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

- ### RECOMMENDATIONS FOR USE
- **USE:** Cut resistant glove. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
 - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
 - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
 - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S	SHO23401	12 pairs per bag
7/M	SHO23402	
8/L	SHO23403	72 pairs per case
9/XL	SHO23404	
10/XXL	SHO23405	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

HEAT AND FIRE EN 407

FOOD CONTACT DIRECTIVE EC 10/2011

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

