# ടноша. | **S-TEX 300**

# FLUORESCENT, CUT RESISTANT LATEX GRIP WITH HAGANE COIL LINER

A comfortable and supple grip glove featuring excellent protection against cuts with Hagane Coil<sup>®</sup> technology and a fluorescent colour for increased visibility in low lighting. SHOWA's patented Hagane Coil<sup>®</sup> technology to provide excellent cut protection.

## FEATURES

- > Cut resistant: Level D (EN388:2016)
- > Breathable open-back design
- > Excellent wet and dry grip
- > Increased visibility in low lighting
- > Form-fitting design for maximum dexterity
- > Hagane Coil<sup>®</sup> technology
- > Wrapped stainless steel liner
- > Natural rubber palm coating
- > Rough textured grip finish
- > Fluorescent colour









## SUITABLE FOR

## **Typical Industries**

- Construction
- Glass
- Masonry
- Mechanical
- Metallurgy
- Plastics

## **Suitable Applications**

- Cutting Dry Objects
- Handling Components with Sharp Edges
- Handling Glass
  Handling Motal Sk
- Handling Metal Sheets

# CERTIFICATION





See overleaf for explanation



# sноша. | S-TEX 300

### **PRODUCT INFORMATION**

	_	
MATERIALS	LINER:	10 gauge Hagane Coil® (Stainless steel/polyester)
	COATING:	Natural latex
COLOUR	Yellow/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
8/M 9/XL 10/XL	SHO2902 SHO2903 SHO2904	10 pairs per bag 120 pairs per case

#### **RECOMMENDATIONS FOR USE**

- USE: Cut resistant glove. Not suitable for thermal, electrical and Chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

### **CERTIFICATION LEGENDS**



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\* 0-4 0-5 0-4 0-4 A-F P

Circular Blade Cut Resistance

Abrasion Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

#### **EUROPE**

#### www.globusgroup.com

- E: sales@globus.co.uk
- **T:** +44 (0)161 877 4747
- F: +44 (0)161 877 4746

#### MIDDLE EAST AND AFRICA

#### www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-S-TEX 300\_0620\_1

EU compliance certificate delivered by the notified body SGS Fimko Oy, Särkiniementie 3, Helsinki, 00211, Finland (Notified Body number 0598)