

ADVANCED CHEMICAL PROTECTION WITH A NITRILE FOAM GRIP

Fully coated nitrile with a nitrile foam palm providing excellent grip in wet and oily conditions whilst protecting from chemicals. The nitrile foam coating provides the grip and the flat nitrile base provides chemical resistance.

FEATURES

- Advanced protection from chemicals with grip performance
- A flexible, robust glove offering great dexterity and good resistance to abrasion
- Nitrile coating provides protection from chemicals, oils, hydrocarbons, benzimes, grease and hexavalent chromium found in concrete
- Foamed nitrile finish provides excellent grip performance and prevents slipping
- An ergonomically designed hand mould replicates the natural curvature of the human hand and thus reduces hand fatigue
- > Unique design for fit and dexterity
- Waterproof













SUITABLE FOR

Typical Industries

- Agriculture
- Chemical
- Construction
- Manufacturing
- Oil and Gas
- Utilities

Suitable Applications

- Changing Oil
- Chemical Handling
- Handling Oily Components
- Maintenance
- Painting
- Refining

CAT III EN 388:2016 EN ISO 3741:2016/Type B 0120 4122X JKL

See overleaf for explanation





PRODUCT INFORMATION

	_			
MATERIALS	LINER:	13 gauge nylon, polyester		
	COATING:	Foam nitrile over nitrile		
COLOUR	Black/green	Black/green		
LENGTH (mm	300 (size de	300 (size dependent)		
CUFF STYLE	Gauntlet	Gauntlet		

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M 9/L 10/XL 11/XXL	SHO3792 SHO3793 SHO3794 SHO3795	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

PROTECTION AGAINST


MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

8

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*




*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxid
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
1	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
Α	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical



EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-379_0620_1