



A BIODEGRADABLE GENERAL PURPOSE GLOVE WITH EXCEPTIONAL DURABILITY, BREATHABILITY AND FINGERTIP SENSITIVITY

The SHOWA 383 is designed to protect workers who switch between general handling and intricate assembly tasks. Featuring Showa EBT technology, It contains a durable, lightweight microporous nitrile coating that delivers excellent levels of grip in dry and light oily conditions.

FEATURES

- › Engineered with Eco Best Technology®, making the glove biodegradable in biologically active landfills (Tested to ASTM D5511, 22.7% biodegradation after 199 days)
- › 13g biodegradable polyester liner is soft and comfortable
- › Embossed nitrile palm finish disperses oil to increase grip and longevity in light oily environments
- › Microporous nitrile coating allows warm air and moisture from inside to escape
- › Exceptional level of tactility and sensitivity
- › A flexible glove designed for easy movement and extended wear
- › Protects from oils, grease and abrasion (8000 cycles)
- › Natural rubber latex free to avoid any risks of allergies



LIGHTWEIGHT
15g LINER



Eco Best Technology

Showa's Eco Best Technology (EBT) is composed of organic material that accelerates the biodegradation of nitrile in biologically active landfills without any sacrifice in performance

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Logistics
- Maintenance
- Manufacturing

Suitable Applications

- Assembly of Dry and Oily Parts
- General Handling
- Handling of Intricate Components
- Light Fabrication
- Mounting and Dismounting of Parts
- Tool Setting

CERTIFICATION



See overleaf for explanation



PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge biodegradable polyester
	COATING:	Foam nitrile
COLOUR	Green	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S	SHO3831	10 pairs per bag 120 pairs per case
7/M	SHO3832	
8/L	SHO3833	
9/XL	SHO3834	
10/XXL	SHO3835	

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)
				Impact Resistance	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

