

INSULATED, TRIPLE DIPPED PVC GAUNTLET WITH CHEMICAL RESISTANCE

A soft and fully coated PVC gauntlet. Seals and protects the hand against chemicals while remaining flexible down to -20

FEATURES

- > Flexible, down to -20°C external temperature
- Impermeable for working in damp or greasy environments
- Patented coating process
- > Fully coated, extra coating over entire hand
- > Forearm protection
- > Rough finish provides a tactile feel and secure grip
- > Anti-bacterial treatment (interior)
- > Special hydrocarbon treatment
- > Fixed, seamless acrylic liner
- > Designed for easy movement and continuous wear









SUITABLE FOR

Typical Industries

- Agriculture
- Chemical
- Food
- Forestry and Fishing
- Logistics
- Oil and Gas
- Transport

Suitable Applications

- Chemical Processing
- Cold Storage
- Cold Weather Work
- Maintenance
- Petrochemistry
- Refining

CAT III EN 388:2016 EN ISO 3741:2016/Type B 5:2016 O120 4221X JKL EN ISO 3745:2016 EN ISO 3745:201







PRODUCT INFORMATION

MATERIALS	LINER:	Cotton, acrylic
	COATING:	PVC
COLOUR	Blue	
LENGTH (mm)	300	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M 9/L 10/XL	SHO4902 SHO4903 SHO4904	10 pairs per bag 60 pairs per case


RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove with cold protection. Not suitable for thermal (heat), electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter




RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

ODE	CHEMICAL	CODE	CHEMICAL
١	Methanol	J	n-Heptane
3	Acetone	K	Sodium hydroxide 40%
	Acetonitrile	L	Sulphuric acid 96%
)	Dichloromethane	M	65% Nitric acid
	Carbon Disulfide	N	99% Acetic acid
	Toluene	0	25% Ammonium hydroxid
5	Diethylamine	P	30% Hydrogen peroxide
1	Tetrahydrofurane	S	40% Hydrofluoric acid
	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
А	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical



COLD HAZARDS EN 511



Convective Cold Resistance



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-490_0620_1