



CUT RESISTANT DURACOIL LINER FULLY COATED NITRILE

Foamed nitrile over fully dipped nitrile coating, over engineered fibre reinforced with HPPE.

FEATURES

- › Cut resistant: Level C (EN 388:2016) / ANSI/ISEA 105-16: A3
- › Increased cut resistance performance due to engineered DURACOIL wrapping technology
- › Fully coated nitrile, with an extra nitrile finish on palm for good grip, aeration and high abrasion resistance (Level 4)
- › Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- › Unique SHOWA ergonomic shape that replicates the natural curve of the human hand for enhanced dexterity and longer use
- › Seamless knit designed to prevent irritation
- › High level of flexibility and dexterity with optimal grip performance in wet & oily conditions
- › Liquid-proof to end of coated area



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Glass
- Manufacturing
- Mechanical

Suitable Applications

- Glass & window fixing
- Mechanical and engineering
- Plumbing
- Dry & oily parts assembly
- Canning
- Mounting & dismantling
- Heavy equipment handling

CERTIFICATION

CAT II



EN 388:2016



4X42C

See overleaf for explanation



577

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, Engineered yarn, polyester
	COATING:	Foam nitrile over nitrile
COLOUR	Grey/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** Cut resistant glove. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S	SHO5771	10 pairs per bag 120 pairs per case
7/M	SHO5772	
8/L	SHO5773	
9/XL	SHO5774	
10/XXL	SHO5775	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)
				Impact Resistance	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
 T: +44 (0)161 877 4747
 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
 T: +971 4 882 9962
 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-577_0620_1