

TRIPLE DIPPED PVC GAUNTLET WITH CUT PROTECTION

A flexible, easy-maintenance, triple dipped PVC gauntlet providing effective protection against cuts and chemicals.

FEATURES

- › Cut resistant: Level B (EN 388:2016)
- › Seals and protects the hand against chemicals while remaining flexible
- › Impermeable for working in damp or greasy environments
- › Fully coated PVC with a rough finish over entire surface provides tactile feel and better grip
- › Greater hygiene
- › Designed for easy movement and continuous wear
- › No irritation by seams in contact with the skin
- › Extended protection on the forearm



SUITABLE FOR

Typical Industries

- Chemical
- Commercial Fishing
- Glass
- Oil and Gas
- Utilities

Suitable Applications

- Bottling
- Chemical Spray and Treatment
- Drainage/Piping
- Guttering
- Painting and Spray Workshops
- Plumbing

CERTIFICATION



See overleaf for explanation

PRODUCT INFORMATION

MATERIALS	LINER:	Aramid
	COATING:	PVC
COLOUR	Blue	
LENGTH (mm)	300	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SHOKV6602	10 pairs per bag 60 pairs per case
9/L	SHOKV6603	
10/XL	SHOKV6604	
11/XXL	SHOKV6605	

RECOMMENDATIONS FOR USE

- USE: Chemical and Cut resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide	C	≥10 min for at least 1 chemical
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofuran	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

