

ALPHA FLOW AMF-3V



R95 DISPOSABLE RESPIRATOR

The Alpha Flow SERIES has been designed to improve comfort and performance whilst maintaining a secure fit. Colour coding the range makes identification simple and easy when varying levels of protection may be required.

FEATURES


- Large surface area ensures very low breathing resistance
- New large exhalation valve which reduces heat build-up and improves wearer comfort
- Colour coded alphamesh shell for ease of identification
- Adjustable headstrap allows for a secure and comfortable fit
- Metal-free - suitable for food industry applications
- Preformed nosebridge eliminates the need for regular adjustment
- Compatible with a wide range of safety eyewear
- Certified to NIOSH R95



PREFORMED NOSEBRIDGE
Ensures excellent fit without the need to keep adjusting while wearing

NEW LARGE EXHALATION VALVE
Reduces heat and moisture build-up

NEW MESH DESIGN
Lightweight, flexible and will not collapse during use



ORDERING INFORMATION

Part Number: AMF-3V

Packaging: 10 singles per box
100 per carton
10 boxes per case

Certification: NIOSH R95 - TC-84A-8092

SUITABLE APPLICATIONS

Recommended applications include:

- Craft Work
- Cutting and Casting of Metals
- Disposal of Toxic Waste
- Hospital
- Iron and Steel Industry
- Laboratory and Disease Control
- Manufacture of Batteries
- Mining
- Pharmaceutical industry
- Textile industry
- Underground Civil Engineering
- Woodworking
- Welding work

ALPHA FLOW AMF-3V



R95 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL
Mesh Shell:	Polypropylene
Filter Outer Layer:	Polypropylene
Filter Inner Layer:	Polypropylene
Filter Internal Media:	Melt-Blown [Polypropylene]
Headstrap:	Woven Elastic [Latex-Free Rubber]
Headstrap Adjuster:	Polypropylene
Exhalation Valve - Valve Housing:	Polypropylene & ABS
Valve Membrane:	Synthetic Rubber
Inner Face Seal:	PVC Foam

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
Respirator	155	70	125
Nosebridge	25	50	35
Headband	700	9	0.4
Headband clip	57	12	9
Valve	43	43	10

CERTIFICATION

Federal Register 42 CFR Part 84, as class R95

This respirator is approved only in the following configuration :

TC	PROTECTION	RESPIRATOR	CAUTIONS AND LIMITATIONS
-	-	AMF-3V	-
84A-8092	R95	X	ABCJMNOPS

1. Protection R95 - Particulate Filter (95% filter efficiency level) effective against all particulate aerosols; time use restrictions may apply.

2. Cautions and Limitations

- A - Not for use in atmospheres containing less than 19.5% oxygen.
- B - Not for use in atmospheres immediately dangerous to life or health.
- C - Do not exceed maximum use concentrations established by regulatory standards.
- J - Failure to properly use and maintain this product could result in injury or death.
- M - All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA and other applicable regulations.

N - Never substitute, modify, add, or omit parts. Use only exact replacements parts in the configuration as specified by the manufacturer.

O - Refer to users instructions, and/or maintenance manuals for information on use and maintenance of these respirators.

P - NIOSH does not evaluate respirators for use as surgical masks.

S - Special or critical User's Instructions and/or specific use limitations apply. Refer to User's Instructions before donning.

RECOMMENDATIONS FOR USE

Protects against soild, liquid and oil particles. Meets NIOSH 42 CFR 84 R95 requirements with a minimum filtration efficiency of 95%.

www.globusgroup.com/gcc T: +971 4 882 9962 E: gcc@globusgroup.com

Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, United Arab Emirates

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Globus EMEA FZE

 **GLOBUS**
EMEA