

Constructed from an extremely durable and lightweight metallised frame, SISINI™ is an extremely robust and versatile option for the majority of applications requiring safety eyewear.




SPORTS
STYLE



SOFT TEMPLE
ENDS



SOFT PVC



ADJUSTABLE
NOSE BRIDGE

KEY FEATURES

- + Sports style design
- + Dual moulded temples with TPE temple ends for maximum fit and comfort
- + Soft adjustable PVC nose bridge
- + Revo and polarised lens tint options available
- + Supplied with a microfibre storage pouch

LENS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00136	2C-1.2 R 1FKN CE	R EN 166 F 2 CE	Impacts, UV Radiations	TECTON 400 K&N Anti-Scratch & Anti-fog / UV400 / Moisture Repellent
AMBER	● RLY00138	2C-1.2 R 1FKN CE		Impacts, UV Radiations	
GREY	● RLY00137	5-2.5 R 1FKN CE		Impacts, UV & Solar Radiations	
REVO	● RLY00139	5-2.5 R 1F CE		Impacts, UV & Solar radiations	FRIDA 400 Anti-scratch + Anti-fog / UV400 / Moisture repellent
POLARISED	● RLY00140	5-3.1 R 1F CE		Impacts, UV & Solar Radiations	

GENERAL SPECIFICATION

LENS BASE	8mm
WEIGHT	27g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Dual lens design
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic / Metal	Co-injected - Durable and flexible, with contour grip
HINGE	Metal	Increased flexibility and strength

LENS & FRAME MARKINGS


LENS MARKINGS

LENS FILTER TYPE:

2, 2C UV | 4 IR filter | 5, 6 Solar filter | 1.7 to 7 Welding filter if no shade number

SCALE NUMBER (SHADE):

1.2 Clear or Amber | 1.4 Blue or I/O Waterproof
1.7 Minimises or I/O | 2.5 Grey or Revo | 3.1 Dark Grey or Mirror

 Identity of manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:


S Increased strength
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
A High energy impact, resists a 6mm, 0.86g ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

8 Short circuit electric arc
9 Molten metal splash
K Resistance to scratches by fine particles
N Resistance to fogging

 Certification mark

FRAME MARKINGS

 Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

S Increased strength
F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s
A High energy impact, resists a 6mm, 0.86 ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE

3 Liquid droplets or splashes
4 Large dust particles > 5 µm
5 Gases and small dust particles < 5 µm
8 Short circuit electric arc
9 Molten metal and hot solids

 Certification marks

USA (ANSI)

LENS:

U6 UV (All lenses) | **L1.3** LED | **L1.7** Solar (I/O, Twilight)
L2.5 Solar (Grey) | **L3** Solar (Dark Grey) | **W4** Infrared lens

LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

AUS (AS/NZS)

LENS MARKINGS:

OCULAR CATEGORY:

0 UV | **1** Solar | **2** Solar
3 Solar | **O** Outdoor untinted

MECHANICAL STRENGTH:

I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

FRAME MARKINGS:

AS/NZS 1337.1: 2010 guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by: UK - CCQS UK LTD. 25 Wilton Road, Pimlico, London, UK, SW1V 1LW [A.B. No. 1105].

EU - CERTOTTICA SCARL., Zona Industriale Villanova, 32013 - Longarone (BL) Italy [N.B. No. 0530]

Authorised Representative [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.



Standard Mark
(SAI Global)

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK

Part of
Globus
GROUP