▲ LPHA A-SERIES - A-2CV





The A SERIES range of respirators combine the benefits of a fold flat respirator with a colour coded alphamesh shell to prevent collapse onto the face. Suitable for protection against a broad range of particulate hazards.

KEY FEATURES

- Electrostatic filter media for low breathing resistance
- Lightweight alphamesh shell designed to maintain shape
- Vertical fold flat design for easy storage in a pocket
- Individually packed
- Continuous loop head strap for easy fitting
- Preformed nose bridge; does not require frequent adjustment
- Colour coded for ease of identification
- Metal free
- Charcoal filter offers protection from nuisance odours and ideal for welding applications
- Conforms to EN 149: 2001 + A1: 2009 FFP2 NR



PREFORMED NOSEBRIDGE Ensures continuity of fit

ADJUSTABLE HEADSTRAP
Wide continuous loop with
adjustment distributes
tension for a secure fit

LOW PROFILE EXHALATION VALVE Helps to reduce heat and moisture build up







ORDERING INFORMATION

Part Number: A-2CV

Packaging: 20 singles per box

10 boxes per case

Certification: EN149: 2001 + A1: 2009

FFP2 NR

SUITABLE APPLICATIONS

Recommended applications include:

- Pharmaceutical
- Food Processing
- Agriculture
- Ship Building/Repair
- Powdered Chemicals
- Woodworking Industry
- Construction
- Metalworking
- Laboratories



LPHA A-SERIES - A-2CV



P2 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL			
Mesh Shell:	Polypropylene			
Filter Outer Layer:	Polypropylene			
Filter Inner Layer:	Polypropylene			
Filter Internal Media:	Melt-Blown [Polypropylene] + Polyester			
Headstrap:	Woven Elastic [Latex-Free Rubber]			
Headstrap Adjuster:	Polypropylene			
Exhalation Valve: Valve Housing:	Polypropylene & ABS			
Valve Membrane:	Synthetic Rubber			
CV Pre-filter:	Activated Carbon Loaded Polypropylene			

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	
Respirator	165	110	170	
Nosebridge	25	40	40	
Headband	700	9	0.4	
Headband clip	57	12	9	
Valve	40	11	40	

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP, United Kingdom. [N.B. No.0086].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149:2001 + A1:2009	Mesh Colour	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	VeryFine / Toxic Dusts / Mists / Fumes	Odours/ Organic Vapours (Below WEL)	Metal Fumes	Oil/Water Based Particulates
FFP1 NR	White	A-1	4						
FFP1 NR	White	A-1V	4						
FFP2 NR	Blue	A-2	10	0				0	
FFP2 NR	Blue	A-2V	10	0				0	
FFP2 NR	Grey	A-2CV	10	0					
FFP3 NR	Orange	A-3V	20	0					

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

