



Ultimus Lite™

CUT RESISTANT GLOVE WITH REINFORCED SPONGE NITRILE PALM

A durable, lightweight glove providing maximum resistance to cuts and protection when handling sharp, slippery objects such as glass and metal.

FEATURES

- › Cut resistant: Level C (EN 388:2016)
- › Excellent grip in damp, oily and dry conditions
- › High levels of flexibility and dexterity
- › Advanced sponge nitrile coating
- › Lightweight 13 gauge liner and enhanced protective padding
- › Reinforced thumb-line enhances durability
- › Breathable liner keeps hand cool and helps to reduce perspiration
- › Elasticated wrist provides a secure fit
- › Seamless liner prevents irritation



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Engineering
- Glass
- Manufacturing
- Metal
- Transport

Suitable Applications

- Bottling/Canning
- Metal Fabrication
- Scaffolding

CERTIFICATION

CAT II



EN 388:2016



4X42C

ANSI/ISEA 105



See overleaf for explanation



Ultimus Lite™

PRODUCTION INFORMATION

MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon
	COATING:	Nitrile Sponge
COLOUR	Black/Light Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKY681	10 pairs per bag
8/M	SKY682	
9/L	SKY683	
10/XL	SKY684	
		120 pairs per case

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777).

UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)

© 2023 Globus (Shetland) Ltd | SKY-DATA-ULTIMUS-LITE-1023,1