



CHEMICAL RESISTANT HEAVY-DUTY FLOCK-LINED NATURAL RUBBER GLOVE

Nero provides mechanical protection as well as resistance from chemicals and cleaning fluids. The pattern on the palm provides grip in slippery and dry handling conditions.

FEATURES

- > Heavy-duty for enhanced protection
- Anti-slip hexagon grip design to palm and fingertips
- > Resistance to water-based chemicals
- > Bacteriostatic and fungistatic additives
- > Pure cotton flock lining absorbs perspiration
- > Chlorinated surface
- > Thickness: 0.65mm for a supple wearing experience
- > Low in soluble proteins
- > Anatomically-shaped to minimise hand fatigue







SUITABLE FOR

Typical Industries

- Agriculture
- Bio-pharmaceutical
- Chemical Processing
- Construction
- Engineering
- Manufacturing
- Utilities

Suitable Applications

- Chemical Handling
- Cleaning
- HGV Drivers
- Maintenance of Equipment
- Medical Research

CERTIFICATION









See overleaf for explanation





△SKYTEC Nero™

PRODUCTION INFORMATION Cotton Flock LINER: MATERIALS COATING: Natural latex COLOUR Black LENGTH (mm) 300

ORDERING DETAILS

CUFF STYLE

SIZE	CODE	PACKAGING
7/S 8/M	SKY871 SKY872 SKY873 SKY874	10 pairs per bag
9/L 10/XL		120 pairs per case

RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

PROTECTION AGAINST

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

Gauntlet



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxid
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
l	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME	
Α	≥30 min for at least 6 chemicals	
В	≥30 min for at least 3 chemicals	
С	≥10 min for at least 1 chemical	

GLOBUS

www.globusgroup.com

EUROPE

E: sales@globus.co.uk +44 (0)161 877 4747

+44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M171SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2023 Globus (Shetland) Ltd | SKY-DATA-NERO-1123_1

Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)