



## PRECISION HANDLING WHEN OPEN FINGERTIP CONTACT IS REQUIRED

Open digit glove for maximum dexterity

### FEATURES

- › Cut resistant: Level A (EN 388:2016)
- › Three open fingers; index, thumb, middle finger
- › Comfortable combination of materials offers excellent work comfort
- › Reinforced on the palm and fingertips for added protection in key areas
- › Flexible
- › Velcro-fastening cuff for a secure fit



### SUITABLE FOR

#### Typical Industries

- Automotive
- Construction
- Engineering
- Manufacturing

#### Suitable Applications

- Component Assembly
- Electrical Tasks (non-live)
- Intricate Mechanical Tasks
- Light Engineering
- Light Fabrication

### CERTIFICATION

CAT II



EN 388:2016



4141A

See overleaf for explanation

**PRODUCTION INFORMATION**

<b>MATERIALS</b>	LINER:	Polyester, spandex, terry clothon thumb
	COATING:	Synthetic Leather/ Neoprene
<b>COLOUR</b>	Grey/Black/Yellow	
<b>LENGTH (mm)</b>	250 (size dependent)	
<b>CUFF STYLE</b>	Elasticated knit wrist	

**ORDERING DETAILS**

SIZE	CODE	PACKAGING
7/S	SKY3901	10 pairs per pack
8/M	SKY3902	
9/L	SKY3903	
10/XL	SKY3904	
11/XXL	SKY3905	60 pairs per case

**RECOMMENDATIONS FOR USE**

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

**CERTIFICATION LEGENDS****MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

**CLASSIFICATION FOR CUT RESISTANCE**

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

**GLOBUS****EUROPE**

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [sales@globus.co.uk](mailto:sales@globus.co.uk)

**T:** +44 (0)161 877 4747

**F:** +44 (0)161 877 4746

**MIDDLE EAST & AFRICA**

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

**T:** +971 4 882 9962

**F:** +971 4 882 9963

**GLOBUS AMERICAS**

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [americas@globusgroup.com](mailto:americas@globusgroup.com)

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)