

The innovative and stylish Cypher is now available in an RX frame providing a complete solution across plano and prescription. The sleek 9 base frame with soft co-injected temples offers high design, maximum comfort and functionality to the wearer. A first-to-market eyewear solution, with a sports wraparound frame.



SPORTS  
STYLE



SOFT ANTI-SLIP  
NOSE BRIDGE



AERO  
TEMPLES

## KEY FEATURES

- + Sports style 9 base frame
- + 6 base curve lens
- + Soft, anti-slip nose bridge
- + Co-injected bi-colour temples with flexible TPE ends enhance overall fit and comfort
- + Unique aero-slotted side arms
- + Also available in plano

	Power Range	Lens Options	Additional Coatings
PRESCRIPTION OPTIONS	+/- 8.00	Single Vision	HC
		Bifocal	AR
		Varifocal	Transition

Lens (eyesize)	Nose piece	Temple Length	Lens
56mm	18mm	130mm	Clear

VERSIONS	LENS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST
GREY FRAME	● CLEAR ○	RLYRX00500	VL 1F CE	R EN 166 FT  Z87	Impacts, UV radiations
CLEAR FRAME	○ CLEAR ○	RLYRX00501	VL 1F CE	R EN 166 FT  Z87	Impacts, UV radiations

## GENERAL SPECIFICATION

FRAME BASE	9mm
LENS BASE	6mm
WEIGHT	31g

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
FRAME	Polycarbonate	Semi-frame design
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	Polycarbonate / Thermoplastic Elastomers (TPE)	Co-injected - Robust and streamline with soft temple tips
HINGE	Polycarbonate / Metal	Increased flexibility and durability

## LENS & FRAME MARKINGS

### LENS MARKINGS

#### LENS FILTER TYPE:

2, 2C UV | 4 IR filter | 5, 6 Solar filter | 1.7 to 7 Welding filter if no shade number

#### SCALE NUMBER (SHADE):

1.2 Clear or Amber 1.4 Blue or I/O Waterproof  
1.7 Minimises or I/O 2.5 Grey or Revo 3.1 Dark Grey or Mirror

Identity of manufacturer

#### OPTICAL CLASS:

1 High optical quality

#### MECHANICAL STRENGTH:

S Increased strength  
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s  
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s  
A High energy impact, resists a 6mm, 0.86g ball at 190m/s  
T Protection against high-speed particles at extreme temperatures

#### PERFORMANCE:

8 Short circuit electric arc  
9 Molten metal splash  
K Resistance to scratches by fine particles  
N Resistance to fogging

Certification mark

### FRAME MARKINGS

Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

#### MECHANICAL STRENGTH:

S Increased strength  
F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s  
B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s  
A High energy impact, resists a 6mm, 0.86 ball at 190m/s  
T Protection against high-speed particles at extreme temperatures

#### PERFORMANCE

3 Liquid droplets or splashes  
4 Large dust particles > 5 µm  
5 Gases and small dust particles < 5 µm  
8 Short circuit electric arc  
9 Molten metal and hot solids

Certification marks

### USA (ANSI)

#### LENS:

U6 UV (All lenses) L1.3 LED L1.7 Solar (I/O, Twilight)  
L2.5 Solar (Grey) L3 Solar (Dark Grey) W4 Infrared lens

#### LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

### AUS (AS/NZS)

#### LENS MARKINGS:

OCULAR CATEGORY:  
0 UV 1 Solar 2 Solar  
3 Solar O Outdoor untinted

#### MECHANICAL STRENGTH:

I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

#### FRAME MARKINGS:

**AS/NZS 1337.1: 2010** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

### CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

**Type-Examination, (Module B), Certificates issued by: UK - CCQS UK LTD.** 25 Wilton Road, Pimlico, London, UK, SW1V 1LW [A.B. No. 1105].

**EU - CCQS Certification Services Limited.,** Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin 15 D15 AKK1, Ireland [N.B. No. 2834]

**Authorised Representative [EU]:** Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.



Standard Mark  
(SAI Global)

[www.riley-eyewear.com](http://www.riley-eyewear.com)

**E:** info@riley-eyewear.com

**T:** +44 (0)161 877 4747

**F:** +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK

