

MEDIUM WEIGHT PALM-COATED NITRILE GLOVE WITH HIGH CUT PROTECTION

Durable high cut resistance glove with thermal resistance up to 100°C/212°F for short contact. Outstanding grip in dry handling conditions.

FEATURES

- › Cut resistance: level F / ANSI A7
- › Mediumweight 10g liner made of para-aramid and steel fibre to protect against high cut risks
- › Nitrile palm coating offers optimum dry grip and protect from oil and water
- › Contact heat protection up to 100°C / 212°F for a short period (15 sec max)
- › Designed for easy movement and continuous wear
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



SUITABLE FOR





Typical Industries

- Public utilities
- Automotive
- Construction
- Glass
- Steel and Metals
- Waste management

Suitable Applications

- Glass Handling
- Metal Fabrication
- Hazardous Recycling
- Paper Manufacturing
- Plastics Manufacturing
- Waste handling

CERTIFICATION

CAT II	EN 388:2016 + A1:2018	EN 407:2020	ANSI/ISEA 105
			
	4X44F	X1XXXX	

See overleaf for explanation

PRODUCTION INFORMATION

MATERIALS	LINER:	10 gauge para-aramid, steel fibre, nylon
	COATING:	Nitrile
COLOUR	Yellow/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00106CB	Each pair single packed, 6 pairs in a polybag
7/S	SKG00106CD	
8/M	SKG00106CF	
9/L	SKG00106CH	
10/XL	SKG00106CJ	
11/XXL	SKG00106CL	120 pairs per case


RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for high thermal (beyond 100C / 212F), electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- **WARNING:** Latex may cause allergies

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



HEAT AND FIRE EN 407

PERFORMANCE LEVELS



CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

ANSI/ISEA PUNCTURE RESISTANCE	
ANSI Puncture Level	Puncture Resistance (newtons)
1	10-19
2	20-59
3	60-99
4	100-149
5	150+

Puncture Resistance (ANSI/ISEA 105): Puncture resistance is determined by the max force that it takes, exerted from a probe, to puncture the fabric.

ANSI/ISEA 105-2016 ABRASION RATING CHART							
Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2024 Globus (Shetland) Ltd | SKY-DATA-REDOX-0424_1

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.