

## Torq Torrent™ Highly Cut-Resistant Reinforced Impact Gloves with Touchscreen Fingers

### Description

Designed for demanding industrial environments, this high cut-resistant impact glove delivers superior protection without compromising flexibility or dexterity. Featuring a robust yet flexible TPR (Thermoplastic Rubber) impact panel, this glove is ideal for workers who need reliable defense against mechanical risks and hand fatigue. The 13-gauge seamless Tuffalene® UHMWPE shell provides robust cut resistance, offering a lightweight yet exceptionally strong barrier against lacerations. The Mach Finish nitrile palm coating ensures a secure grip even in oily or wet conditions, enhancing control and safety.



### INDUSTRY

|              |                     |
|--------------|---------------------|
| Automotive   | Highway Work        |
| Construction | Aircraft Operations |
| Oil and Gas  | Highway Repairs     |
| Maritime     | General Labor       |

ITEM **SKG00081F** SIZES **7(S)-12(3XL)**



### Features

- 13-gauge Tuffalene® UHMWPE shell is comfortable and dexterous
- Abrasion-resistant Mach Finish nitrile offers excellent grip in wet and oily conditions
- Flexible TPR impact protection over the fingers and metacarpal bones provides tough protection
- Ergonomically designed TPR and curved fingers follow the natural hand movement and reduce hand fatigue
- TPR zones are sewn to the liner for increased resistance
- Touchscreen compatible fingertips allow workers to operate devices without removing gloves
- Reinforced thumb crotch increases durability in vulnerable, high-wear areas for longer glove life
- Contact heat protection up to 100°C / 212°F for a short period (15 sec max)
- Knit wrist with hook-and-loop closure allows users a secure and comfortable fit
- EN 388:2016 + A1:2018 Levels: 4X43FP
- EN 407:2020 Levels: X1XXXX

### Meets ANSI/ISEA 105-2016 standard

- Cut Level A5
- ASTM F2992-15 Results = 2,820 grams
- Abrasion Level 6
- Puncture Level 3
- Puncture Results: 75 Newtons

### Meets ANSI/ISEA 138-2019 standard

- Impact Level (Fingers/Thumb): 2
- Impact Level (Knuckles): 2
- Impact Level (Overall): 2

### Specifications

| SHELL                               | SHELL COLOR     | GAUGE                 | COATING  | COATING COLOR | COATING TYPE     | FINISH  | REINFORCED AREA | IMPACT PROTECTION | TOUCH SCREEN |
|-------------------------------------|-----------------|-----------------------|----------|---------------|------------------|---------|-----------------|-------------------|--------------|
| Tuffalene® UHMWPE                   | Salt-and-Pepper | 13-Gauge              | Nitrile  | Black         | Palm             | Sandy   | Thumb Saddle    | TPR               | Yes          |
| CUFF                                | CUT             | ASTM F2992-15 RESULTS | ABRASION | PUNCTURE      | PUNCTURE RESULTS | IMPACT  | EN 388 LEVELS   | EN 407 LEVELS     |              |
| Knit Wrist with Hook-and-Loop Strap | Level A5        | 2,820 Grams           | Level 6  | Level 3       | 75 Newtons       | Level 2 | 4X43FP          | X1XXXX            |              |

### Packaging

| QUANTITY       |           | 7(S)           | 8(M)           | 9(L)           | 10(XL)         | 11(2XL)        | 12(3XL)        |
|----------------|-----------|----------------|----------------|----------------|----------------|----------------|----------------|
| SKU            |           | SKG00081FD     | SKG00081FF     | SKG00081FH     | SKG00081FJ     | SKG00081FL     | SKG00081FN     |
| INNER PACK UPC | 12/PACK   | 810168165073   | 810168162805   | 810168162843   | 810168162812   | 810168162829   | 810168162836   |
| CASE GTIN      | 6 PK/CASE | 10810168165070 | 10810168162802 | 10810168162840 | 10810168162819 | 10810168162826 | 10810168162833 |
| OVERCAST COLOR |           | White          | Green          | Brown          | Yellow         | Gray           | Blue           |