

DUAL LINED GLOVE WITH OIL PROTECTION

A double lined glove with a terry outer that absorbs oils to improve grip and feel whilst the inner liner protects against the ingress of contaminants. Excellent protection from the cold and resistance to heat.

FEATURES

- › Machine knitted seamless terry outer with a comfortable oil resistant coated nylon inner liner
- › Terry outer absorbs oil to improve grip and feel
- › Inner lining is made of nylon and palm coated with non-porous PVC
- › Excellent heat resistance and protection from the cold
- › Resistant to contact heat up to 250°C
- › Anatomically designed for comfort and fit
- › Breathable nylon inner for reduced perspiration and skin irritation
- › Sanitized® antimicrobial finish provides extra freshness
- › Elasticated wrist provides a secure fit
- › Grey colouring helps extend it's wearable life



SUITABLE FOR

Typical Industries

- Food
- Glass
- Manufacturing
- Metals
- Oil & Gas
- Paper

Suitable Applications

- Cardboard Handling
- Cold Storage
- Heavy Engineering
- Sheet Metal Handling

CERTIFICATION

CAT II	EN 388:2016	EN 511:2006	EN 407:2004
	2231X	X1X	X2XXXX

See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	Cotton / Nylon / PVC
	COATING:	NA
COLOUR	Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS		
SIZE	CODE	PACKAGING
7/S	SKY071	10 pairs per pack
8/M	SKY072	
9/L	SKY073	
10/XL	SKY074	
11/XXL	SKY075	100 pairs per case

- ### RECOMMENDATIONS FOR USE
- **USE:** Thermal resistant glove. Not suitable for chemical or electrical protection. Do not use near moving machines if there is a risk of entanglement
 - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
 - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
 - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4	0-5	0 or 1
Convective Cold Resistance	Contact Cold Resistance	Water Permeability

HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4	0-4	0-4	0-4	0-4	0-4
Burning Behaviour	Contact Heat Resistance	Convective Heat Resistance	Radiant Heat Resistance	Resistance to Small Drops Of Molten Metal	Resistance to Large Splashes of Molten Metal

GLOBUS

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA
EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15V2P, Republic of Ireland. (Notified Body No. 2777)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.