

**ORANGE SINGLE USE GLOVE WITH GRIP PATTERN, 100% NITRILE, POWDER FREE, 240MM LONG**

High performance, powder-free, orange nitrile single use glove with diamond grip pattern technology. Provides outstanding grip performances and chemical protection.

**FEATURES**

- › High quality nitrile, soft and durable
- › Palm thickness 0.23mm (9mil), weight: 8.5g size M
- › High resistance to penetration and projections of many chemicals
- › Diamond grip pattern technology on both side offering outstanding grip properties in all conditions
- › Powder-free, latex free, non-sterile, AQL 1.5
- › Chlorinated inside to offer more comfort and reduce friction when donning
- › Antistatic properties due to inherent antistatic properties of nitrile
- › Lasts up to 5 times longer than regular single use gloves in industrial applications
- › Ambidextrous for easy and quick donning



**SUITABLE FOR**

**Typical Industries**

- Aerospace
- Chemical
- Electronics
- Automotive
- Manufacturing
- Oil and Gas

**Suitable Applications**

- Chemical Handling
- Handling Oily Components
- Light Assembly
- Engineering
- Repair and Finishing

**CERTIFICATION**

CAT III	EN ISO 374-1:2016/ Type B	EN ISO 374-5:2016	
2777	KOPT	Virus	

See overleaf for explanation

## PRODUCTION INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	–
COLOUR	Orange	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

## ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKG00925GD	100 singles per box (90 singles on size XXL) 10 boxes per case
8/M	SKG00925GF	
9/L	SKG00925GH	
10/XL	SKG00925GJ	
11/XXL	SKG00925GL	

## RECOMMENDATIONS FOR USE

- **USE:** Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## CERTIFICATION LEGENDS



**PROTECTION AGAINST MICRO-ORGANISMS EN 374-5**  
VIRUS = Glove has passed ISO 16604:2004 (method B)



**FOOD CONTACT DIRECTIVE 2002 / 72 EC**



**RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016**

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide	C	≥10 min for at least 1 chemical
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofuran	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

# GLOBUS

### EUROPE

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [sales@globus.co.uk](mailto:sales@globus.co.uk)

**T:** +44 (0)161 877 4747

**F:** +44 (0)161 877 4746

### MIDDLE EAST & AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

**T:** +971 4 882 9962

**F:** +971 4 882 9963

### GLOBUS AMERICAS

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [americas@globusgroup.com](mailto:americas@globusgroup.com)

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777)