∆SKYTEC Teal[™]

SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, 240MM LONG, 0.12MM THICK

Premium performance, powder-free, nitrile single use glove. Dual certified (Industrial and Medical), extremely strong and higher chemical and puncture resistance than regular nitrile disposables.

FEATURES

- > 100% premium quality nitrile
- > Palm thickness 0.12mm (5 mil)
- > High resistance to penetration and projections of many chemicals
- > Chlorinated inside to offer more comfort and reduce friction when donning
- > Powder-free, latex free, non-sterile, AQL 1.5
- > Approved for food handling
- > Dual labelling: PPE and medical
- Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)
- Antistatic properties due to inherent antistatic properties of nitrile



SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Food
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Food Preparation
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION



See overleaf for explanation



∆SKYTEC Teal[™]

PRODUCTION INFORMATION

	LINER:	Nitrile
MATERIALS	COATING:	-
COLOUR	Green	
LENGTH (mm)	240 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
5½-6/XS 6½-7/S 7½-8/M 8½-9/L 9½-10/XL 10½ - 11/XXL	SKYTEALO SKYTEAL1 SKYTEAL2 SKYTEAL3 SKYTEAL4 SKYTEAL5	100 singles per box 10 boxes per case

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*								
0-4	0-5	0-4	0-4	A-F	Р			
				5	I Impact Resistance ht Blade Cut Resistance (EN ISO: 13997)			
Puncture Resistance								
Tear Resistance								
Circular Blade Cut Resistance								
Abrasion Resistance								

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

LE TO CITEMICAE PERMEATION - EN ISO 374.2010							
EMICAL thanol	CODE J	CHEMICAL n-Heptane	TYPE OF GLOVES	BREAKTHROUGH TIME			
etone etonitrile hloromethane	K L M	Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide	А	≥30 min for at least 6 chemicals			
bon Disulfide uene thylamine	N O P		В	≥30 min for at least 3 chemicals			
rahydrofurane yl acetate	ne S 40% Hydrofluorio	30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	С	≥10 min for at least 1 chemical			

GLOBUS

CODE

R

D

G H CHE Met

Ace

Ace

Dich Carl

Tolu Diet

Tetr

Eth

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15 YN2P. Republic of Ireland. (Notified Body No. 2777)

GLOBUS AMERICAS

PROTECTION AGAINST

FOOD CONTACT DIRECTIVE 2002 / 72 EC

MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

S

www.globusgroup.com

E: americas@globusgroup.com

© 2023 Globus (Shetland) Ltd | SKY-DATA-TEAL-1123_1

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.