# **SKYTEC** Sapphire Supreme

# ULTRA LIGHTWEIGHT, EXTREME CUT RESISTANT GLOVES WITH NITRILE **MICRO FOAM**

Using the latest innovation, Sapphire Supreme is a very light weight glove (18 gauge) providing outstanding cut protection and high dextertity in the most risky applications. Thin, Breathable and long lasting coating, ideal for all precise applications.

#### **FEATURES**

- > Cut resistant: Level F / ANSI A6
- > 18 gauge seamless liner offers flexibilty, comfort and high fingertip sensitivity
- > HPPE on the inside provides comfort and protection
- > Specific metal fibre and Nylon on the outside, fully encapsulated enable extreme cut protection against burrs and sharp edges.
- > Micro foam nitrile coating gives good grip and dexterity while allowing warm air and moisture from inside to escape, keeping your hands dry and comfortable
- > Reinforced thumb crotch enhances durability
- > Touchscreen capabilities to allow usage with screen devices
- > Breathable back of hand to reduce perspiration
- > Seamless knit prevents irritation
- > Elasticated wrist provides a secure fit











## **SUITABLE FOR**

#### **Typical Industries**

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Transport

#### **Suitable Applications**

- Assembly
- Handling sharp and greasy parts
- Machining
- Bodywork
- Precision mechanics

## **CERTIFICATION**



See overleaf for explanation







# **SKYTEC** Sapphire Supreme

#### **PRODUCTION INFORMATION**

MATERIALC	LINER:	18 gauge HPPE, metal fiber, nylon	
MATERIALS	COATING:	Micro foam nitrile	
COLOUR	Grey/Black		
LENGTH (mm)	250 (Size Dependent)		
CUFF STYLE	Elasticated knit wrist		

#### ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKYG00001TD SKYG00001TF SKYG00001TH SKYG00001TJ SKYG00001TL	10 pairs per paper wrap 120 pairs per case


#### **RECOMMENDATIONS FOR USE**

- USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

#### **CERTIFICATION LEGENDS**



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\*



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

	CLASSIFICATION FOR CUT RESISTANCE			
	Measured breakthrough time	Permeation performance index (grams)		
	A1	≥ 200		
	A2	≥ 500		
	A3	≥ 1000		
	A4	≥ 1500		
	A5	≥ 2200		
	A6	≥ 3000		
	A7	≥ 4000		
	A8	≥ 5000		
4	ΔΟ	> 6000		

# GLOBUS

### **EUROPE**

#### www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)1618774746

#### **MIDDLE EAST & AFRICA**

#### www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +97148829962

F: +97148829963

### **GLOBUS AMERICAS**

### www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-SAPP-SUPREME-1123\_1

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)