## **ASKYTEC** TRC715


# A LIGHTWEIGHT NITRILE FOAM COATED GLOVE WITH STEEL FIBRE AND RECYCLED POLYESTER

Outstanding cut resistance allowing protection in the most risky applications. Breathable, long lasting and flexible glove providing excellent grip in oily conditions

#### **FEATURES**

- > Cut resistant: Level E / ANSI A5
- A flexible and comfortable glove offering great dexterity
- ▶ HPPE on the inside provides comfort and protection
- > Fully encapsulated steel with recycled polyester with recycled polyeste on the outside strengthens the protection against burrs and sharp edges
- Micro foam nitrile coating gives exceptional grip while allowing warm air and moisture from inside to escape, keeping your hands dry and comfortable
- > Reinforced thumb crotch enhances durability
- > Seamless knit prevents irritation
- > RCS (Recycled Claim Standard) certified
- > 1 pair = 1 PET bottle of 500ml recycled
- > 26g of CO<sub>2</sub> reduced vs virgin polyester alternative













#### **SUITABLE FOR**

#### **Typical Industries**

- Automotive
- Construction
- Maintenance
- Manufacturing
- Metal Industry

#### **Suitable Applications**

- Assembly
- Handling sharp and oily parts
- Machining
- Glass handling
- Bodywork

#### **CERTIFICATION**








See overleaf for explanation





## **ASKYTEC** TRC715

### PRODUCTION INFORMATION

MATERIALS	LINER:	13 gauge HPPE, steel fibre, recycled polyester
	COATING:	Foam nitrile
COLOUR	Green/black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00016EB SKG00016ED SKG00016EF SKG00016EH SKG00016EJ SKG00016EL	10 pairs per paper wrap 120 pairs per case


#### **RECOMMENDATIONS FOR USE**

- USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

#### **CERTIFICATION LEGENDS**



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\*



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE			
Measured breakthrough time	Permeation performance index (grams)		
A1	≥ 200		
A2	≥ 500		
A3	≥ 1000		
A4	≥ 1500		
A5	≥ 2200		
A6	≥ 3000		
A7	≥ 4000		
A8	≥ 5000		
A9	> 6000		

CLASSIEICATION FOR CUT DESISTANCE

#### **GLOBUS**

#### **EUROPE**

#### www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)1618774747 F: +44 (0)1618774746

#### MIDDLE EAST & AFRICA

#### www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

### **GLOBUS AMERICAS**

#### www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-TRC715-1123\_1

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575) and the contraction of the con