



# Sapphire Silver™

## MEDIUM CUT RESISTANCE AND EXCELLENT GRIP IN DRY AND GREASY CONDITIONS

Affordable medium cut resistant glove with spun HPPE offering a high degree of comfort and dexterity. PU coating protects the hand from grease delivering effective long lasting grip.

### FEATURES

- › Cut resistant: Level B / A2
- › A flexible and comfortable glove offering great dexterity
- › Durable polyurethane palm coating ensures good protection against abrasion
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



### SUITABLE FOR

#### Typical Industries

- Aerospace
- Automotive
- Construction
- Manufacturing
- Railways
- Transport

#### Suitable Applications

- Bottling/Canning
- Mechanical Inspection
- Metal Fabrication
- Paint Spraying

### CERTIFICATION



See overleaf for explanation



# Sapphire Silver™

## PRODUCTION INFORMATION

MATERIALS	LINER:	13 gauge HDPE, glass fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

## RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00078FB	10 pairs per paper wrap
7/S	SKG00078FD	
8/M	SKG00078FF	
9/L	SKG00078FH	
10/XL	SKG00078FJ	120 pairs per case
11/XXL	SKG00078FL	

## CERTIFICATION LEGENDS



### MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

### CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

## GLOBUS

### EUROPE

[www.globusgroup.com](http://www.globusgroup.com)

E: [sales@globus.co.uk](mailto:sales@globus.co.uk)

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

### MIDDLE EAST & AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

E: [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

T: +971 4 882 9962

F: +971 4 882 9963

### GLOBUS AMERICAS

[www.globusgroup.com](http://www.globusgroup.com)

E: [americas@globusgroup.com](mailto:americas@globusgroup.com)

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)  
 UKCA Type-Examination Certificate issued by CCQS UK Ltd, 25 Wilton Rd, Pimlico, London SW1V 1LW, United Kingdom. [UK Approved Body No. 1105].

© 2023 Globus (Shetland) Ltd | SKY-DATA-SAPP-SILVER-1023,1