∠SKYTEC TX830[™]

SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, SILICONE FREE, 300MM LONG, 0.20MM THICK

Premium performance, powder-free, extended cuff nitrile single use glove. Extremely strong and high resistance to chemicals.

FEATURES

- > High quality nitrile, soft and durable
- > High resistance to penetration and projections of many chemicals
- > Palm thickness 0.20mm (8 mil), weight: 9.2g size M
- > Extended cuff (300mm length) to protect the forearm
- > Textured finish on palm to enhance grip
- > Powder-free, latex free, non-sterile
- Chlorinated inside to offer more comfort and reduce friction when donning
- > AQL 0.65
- Antistatic properties due to inherent antistatic properties of nitrile
- > Silicone free

SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION



See overleaf for explanation



∧SKYTEC TX830[™]

PRODUCTION INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	_
COLOUR	Blue	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00830DB SKG00830DD SKG00830DF SKG00830DH SKG00830DJ SKG00830DL	50 singles per box 10 boxes per case

CERTIFICATION LEGENDS



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)



A B C D

Н

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE

К

М

0

S

DDE	CHEMICAL
	Methanol
	Acetone
	Acetonitrile
	Dichloromethan
	Carbon Disulfide
	Toluene
	Diethylamine
	Tetrahydrofuran
	Ethyl acetate

n-Heptane Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide 40% Hydrofluoric acid

CHEMICAL

А В

37% Formaldehvde

≥30 min for at least 6 chemicals ≥30 min for at least 3 chemicals ≥10 min for at least С 1 chemical

TYPE OF BREAKTHROUGH

GLOBUS

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- +44 (0)161 877 4747 T:
- +44 (0)161 877 4746 **F**:

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15 YN2P. Republic of Ireland. (Notified Body No. 2777)

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

© 2023 Globus (Shetland) Ltd | SKY-DATA-TX830-1123_1

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for Mechanical , thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use