

**CUT RESISTANT, THERMAL, WATER REPELLENT FULLY COATED LATEX GLOVE**

A fully coated glove combining thermal properties and cut resistance with an open cuff for easy donning and doffing. Ideal for sharp handling in cold and wet environments.

**FEATURES**

- › Cut resistant: Level D (EN 388:2016)
- › Cut resistant liner protects against sharp parts and the thermal liner provides insulation at cold temperatures
- › Flexible and robust glove offering a good level of dexterity
- › Water repellent for working in wet environments
- › Protects the hand from liquids with optimal long lasting grip
- › Open cuff (cut-out in wrist area) to ease removal of the glove
- › No irritation by seams in contact with the skin



**SUITABLE FOR**





**Typical Industries**

- Construction
- Glass
- Public Works
- Transportation
- Waste Management

**Suitable Applications**

- Sharp and Wet Parts Handling
- Scaffolding

**CERTIFICATION**

CAT II	EN 388:2016 + A1:2018	EN 511:2006	ANSI/ISEA 105
			
	3X33D	X1X	

See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon, acrylic
	COATING:	Double coated crinkle latex over latex
COLOUR	Grey/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Open cuff	

ORDERING DETAILS		
SIZE	CODE	PACKAGING
7/S	SKY00131	10 pairs per bag
8/M	SKY00132	
9/L	SKY00133	60 pairs per case
10/XL	SKY00134	
11/XXL	SKY00135	

- ### RECOMMENDATIONS FOR USE
- USE: Cold and cut resistant glove. Not suitable for thermal (heat), electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
  - STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
  - CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
  - LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
  - WARNING: Latex may cause allergies

### CERTIFICATION LEGENDS

**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance		Puncture Resistance	Impact Resistance
			Straight Blade Cut Resistance (EN ISO: 13997)		
			Tear Resistance		

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

**COLD HAZARDS EN 511 PERFORMANCE LEVELS**

0-4	0-5	0 or 1
Convective Cold Resistance		Water Permeability
Contact Cold Resistance		

## GLOBUS

**EUROPE**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** sales@globus.co.uk  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

**MIDDLE EAST & AFRICA**  
[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)  
**E:** gcc@globusgroup.com  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963

**GLOBUS AMERICAS**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA