△SKYTEC Ninja Silver+™

CUT RESISTANCE AND EXCELLENT GRIP IN OILY AND DRY CONDITIONS

Excellent cut resistance whilst maintaining a high degree of comfort and dexterity. PU coating protects the hand from oils and grease delivering effective long lasting grip.

FEATURES

- > Cut resistant: Level C (EN 388:2016)
- > Excellent grip in wet, oily or dry conditions
- > High durability resistance to rips and abrasion
- Glove retains flexibility despite its high protection levels
- Machine knitted liners made with high performance polyethylene and glass yarn to provide a good cut resistance barrier, while offering dexterity and comfort
- > Coated with polyurethane on palm up to fingers
- > Breathable liner helps keep hands cool







SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Manufacturing
- Railways
- Transport

Suitable Applications

- Bottling/Canning
- Mechanical Inspection
- Metal Fabrication
- Paint Spraying

CAT II EN 388:2016 ANSI/ISEA 105 AX43C

See overleaf for explanation





△SKYTEC Ninja Silver+™

PRODUCTION INFORMATION

MATERIALO	LINER:	13 gauge HPPE, glass fibre, nylon	
MATERIALS	COATING:	Polyurethane (PU)	
COLOUR	Grey		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Elasticated knit wrist		

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL	SKY290 SKY291 SKY292 SKY293 SKY294	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016

Impact Resistance
Straight Blade Cut Resistance (EN ISO: 13997)
Puncture Resistance
Tear Resistance
Circular Blade Cut Resistance
Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE				
Measured breakthrough time	Permeation performance index (grams)			
A1	≥ 200			
A2	≥ 500			
A3	≥ 1000			
A4	≥ 1500			
A5	≥ 2200			
A6	≥ 3000			
A7	≥ 4000			
A8	≥ 5000			
A9	> 6000			

	ANSI/I	SEA 10:	5-2016	ABRASIO	N RATING	CHART	
Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

ANSI/ISEA PUNCTURE RESISTANCE				
	Puncture Resistance (newtons)			
1	10-19			
2	20-59			
3	60-99			
4	100-149			
5	150+			

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)1618774747 F: +44 (0)1618774746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

© 2023 Globus (Shetland) Ltd | SKY-DATA-NINJA-SILVER+-1123_1