

**IMPACT PROTECTION WITH CUT RESISTANCE**

A flexible impact resistant glove with TPR protection zones giving great grip in wet, oily and dry conditions. Provides extremely high level (F) of cut resistance as part of the EN 388:2016 standard.

**FEATURES**

- › Cut resistant: Level F (EN 388:2016)
- › A robust single-piece synthetic leather palm for heightened durability and anti-slip grip
- › Durable multilayer fabric on palm providing high cut and abrasion resistance
- › Dense and flexible moulded TPR protection zones on knuckle, fingers, thumb and back of hand reduce hand fatigue and protect against impact
- › Resistance to contact heat up to 250°C
- › Neoprene cuff resists snagging and offers a comfortable and secure fit
- › Kevlar® stitches on palm for increased lifetime
- › Anatomical design helps prevent hand fatigue
- › Identification tag integrated into cuff



**SUITABLE FOR**

**Typical Industries**

- Construction
- Metal Fabrication
- Mining
- Oil and Gas
- Transportation

**Suitable Applications**

- Assembly
- Cargo Handling
- Demolition
- Drilling
- Heavy Construction
- Mining Extraction

**CERTIFICATION**



See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	Laminated polyester Lycra with moulded TPR protection
	COATING:	Synthetic leather with red ARMORTEX abrasion resistant fabric and knitted cut resistant fabric
COLOUR	Yellow/Black/Red	
LENGTH (mm)	260mm	
CUFF STYLE	Neoprene cut and sewn	

- ### RECOMMENDATIONS FOR USE
- **USE:** General handling glove with cut and impact protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
  - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
  - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
  - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

### ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SKY922	10 pairs per bag
9/L	SKY923	
10/XL	SKY924	60 pairs per case
11/XXL	SKY925	

### CERTIFICATION LEGENDS

**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

**HEAT AND FIRE EN 407 PERFORMANCE LEVELS**

0-4	0-4	0-4	0-4	0-4	0-4
Burning Behaviour	Contact Heat Resistance	Convective Heat Resistance	Radiant Heat Resistance	Resistance to Small Drops Of Molten Metal	Resistance to Large Splashes of Molten Metal

## GLOBUS

**EUROPE**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** sales@globus.co.uk  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

**MIDDLE EAST & AFRICA**  
[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)  
**E:** gcc@globusgroup.com  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963

**GLOBUS AMERICAS**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** americas@globusgroup.com