



CUT RESISTANT SLEEVE FOR FULL ARM PROTECTION

Comfortable 22 inch cut resistant sleeve with a secure, adjustable fastening.

FEATURES

- > Full arm cut protection from wrist to shoulder
- > Cut resistant: Level D (EN 388:2016)
- > Lightweight 13 gauge construction
- > Thinner material on palm and back of hand improves comfort and dexterity when combined with a glove
- > Adjustable VELCRO® Brand hook and loop fastening strap for a secure fit
- > Thumbhole prevents sleeve from rising up and exposing the wrist
- > Light thermal protection up to 100°C for a short period
- > Soft and comfortable to wear
- Ambidextrous
- > Length: 22 inches (55cm)







SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Glass
- Logistics
- Plastics
- Steel

Suitable Applications

- Castings
- Ductwork
- Engine Servicing
- Glass Handling
- HVAC
- Metalworking
- Sheet Metal Handling

CERTIFICATION

CAT II EN 388:2016







See overleaf for explanation







PRODUCTION INFORMATION

MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon, spandex
	COATING:	N/A
COLOUR	Grey	
LENGTH (mm)	560	
CUFF STYLE	Elasticated with VELCRO® Brand hook and loop fastener	

ORDERING DETAILS

SIZE	CODE	PACKAGING
22″	SKY1022	10 pairs per bag
		120 pairs per case

RECOMMENDATIONS FOR USE

- USE: Cut resistant sleeve. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use


CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



HEAT AND FIRE EN 407



CLASSIFICATION FOR CUT RESISTANCE				
Measured breakthrough time	Permeation performance index (grams)			
A1	≥ 200			
A2	≥ 500			
A3	≥ 1000			
A4	≥ 1500			
A5	≥ 2200			
A6	≥ 3000			
A7	≥ 4000			
A8	≥ 5000			
A9	> 6000			

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-KOPTER-1123_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777).
UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com