KYTE

# **SKYTEC CH102**

## DURABLE, OIL-RESISTANT, TRIPLE-DIPPED PVC GLOVE WITH EXTENDED CUFF

SKYTEC CH102 features a soft comfortable cotton lining and a rough textured PVC coating that ensures grip in contact with oils and chemicals. Extended cuff to protect the entire arm.

## FEATURES

- A flexible, soft glove that absorbs perspiration, for ultra comfortable extended wear and with good mechanical resistance
- > Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- > Excellent abrasion resistance (EN388 Level 4)
- > Surface provides tactile feel and better grip
- > Designed for easy movement and continuous wear
- > No irritation by seams in contact with the skin
- > Arm entirely protected with the extended cuff
- > Thickness: 1.3mm





## SUITABLE FOR

## **Typical Industries**

- Agriculture
- Automotive
- Chemical
- Construction
- Petrochemical
- Public Utilities

## Suitable Applications

- Commercial Fishing
- Chemical Handling
- Decontamination Work
- Dipping
- Drain/Sewer Cleaning
- Engine Servicing

## CERTIFICATION



See overleaf for explanation



## **SKYTEC CH102**

### **PRODUCTION INFORMATION**

	LINER:	Cotton		
MATERIALS	COATING:	PVC		
COLOUR	Dark blue			
LENGTH (mm)	600 (Size dependant)			
CUFF STYLE	Gauntlet			

## **ORDERING DETAILS**

SIZE	CODE	PACKAGING
7/S 8/M	SKG00069DD SKG00069DF	12 pairs per bag
9/L 10/XL 11/XXL	SKG00069DH SKG00069DJ SKG00069DL	48 pairs per case

## **CERTIFICATION LEGENDS**

	MECHANICAL HAZARDS EN 388:2016						CLASSIFICATION FOR CUT RESISTANCE								
	PERFORMANCE LEVELS*							Measured breakthrough time			Permeation performance index (grams)				
$\smile$	0-4 0-5 0-4 0-4 A-F P							A1 A2			≥ 200 ≥ 500				
							A3			≥ 1000					
	Straight Blade Cut Resistance (EN ISO: 13997) Puncture Resistance Tear Resistance							A4		≥ 1500					
							AS			≥ 2200					
	Circular Blade Cut						A6			≥ 3000					
	Abrasion Resistance						A7			≥ 4000					
								A8 A9			≥ 5000				
	*If tests are not performed or	are not applica	ble, 'X' will be placed instead of a nu	umber/letter			· · · · ·	49			> 6000				
									ANSI/ISEA 105-2016 ABRASION RATING C						
		RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016							1	2	3	4			
$\checkmark$	CODE CHEMICAL A Methanol B Acetone C Acetonitrile D Dichloromethane	J		TYPE OF GLOVES	BREAKTHROUGH TIME		Gram Load	500	500	500	500	1000			
		K L M	Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid	А	≥30 min for at least 6 chemicals		Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000			
	E Carbon Disulfide F Toluene	N O	99% Acetic acid 25% Ammonium hydroxide	В	≥30 min for at least 3 chemicals										
	H Tetrahydrofurane		30% Hydrogen peroxide 40% Hydrofluoric acid	>10 mi	≥10 min for at least		A	NSI/ISE	A PUNC	TURE RE	SISTANC	CE			
	I Ethyl acetate	T	37% Formaldehyde	С	1 chemical		ANSI Puncture Level			Puncture Resistance (newtons)					
	i Eulyracetate						1			10-19					
	i Euryracetate						2			20-59					
	i Euryi acetate							2							
	PROTECTION AGAINS	г		FOO	D CONTACT			3			60-99				
<u>B</u>	,				D CONTACT CTIVE 2002 / 72 EC						60-99 100-14 150+	19			

## GLOBUS

#### **EUROPE**

#### www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

## **MIDDLE EAST & AFRICA**

#### www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA EU Type-Examination Certificate issued by CTC, 4 rue Hermann Frenkel 69367 Lyon cedex 07 FRANCE. (Notified Body No. 0075)

## **RECOMMENDATIONS FOR USE**

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## **GLOBUS AMERICAS**

#### www.globusgroup.com

E: americas@globusgroup.com

© 2024 Globus (Shetland) Ltd | SKY-DATA-CH102-0724\_2

6 1000

≥20.000

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.